

Farmall A

		Farmall 85 A	Farmall 95 A	Farmall 105 A	Farmall 115 A
Engine name / size / number of cylinders	(- / cm ³ / -)	F5C /3,400 / 4			
Emissions level		Tier 4A / Stage IIIB			
Rated power	(hp[CV])	86	99	107	114
Maximum torque	(Nm)	351	407	444	457
Diesel tank capacity	(litres)	121			
Transmission type (1)		12 x 12 Synchroshift with mechanical shuttle - standard			
Max. Speed	(kph)	40			
Transmission type (2)		12 x 12 Synchroshift with power shuttle			
	(kph)	40			
Transmission type (3)		12 x 12 Synchroshift with mechanical shuttle and creeper			
		40			
Maximum number of hydraulic remotes		3 mechanical and two mechanical mid-mounts			
Maximum hydraulic flow	(Litres/minute)	63			
Maximum rear lift capacity	(kg)	4,700			
PTO Speeds		540, 540E or 540, 1000 or 540, 540E (ground speed optional)			
Maximum permissible weight	(kg)	5,800	6,000	6,500	6,500
Overall length including weight pack and rear linkage	(mm)	4,320			
Minimum width	(mm)	2,110			
Overall height	(mm)	2,640	2,665	2,690	2,690
Wheelbase	(mm)	2,280			