

T4 PowerStar

		T4.55	T4.65	T4.75
Engine name / Capacity / number of cylinders	(- / cm ³ / -)	F5C / 3400 / / 4		
emissions level		Tier4B - Stage 4		
Rated power	[kW/hp(CV)]	43/58	48/65	55/75
Maximum torque	(Nm)	244	275	309
Diesel tank capacity	(litres)	90		
Transmission type (1)		Synchro Shuttle™ transmission		
Maximum Speed	(kph)	30 / 40		
Transmission type (2)		Hydraulic Powershuttle transmission		
Maximum Speed	(kph)	30 / 40		
Transmission type (3)		Synchro Shuttle™ transmission with Optional Creeper		
Maximum Speed	(kph)	30 / 40		
Transmission type (4)		Hydraulic Powershuttle transmission with Optional Creeper		
Maximum Speed	(kph)	30 / 40		
Maximum number of hydraulic remotes and diverter		3 + 1 rear and two mid-mounts		
Main pump flow	(lpm)	47.5	47.5	47.5
Maximum rear lift capacity	(kg)	2760	2760	2760
PTO Speeds		540, 540 or 540E, Ground speed		
Maximum permissible weight 2WD / 4WD	(kg)	4500 / 4800		
Overall length including front support to rear linkage	(mm)	3884		
Minimum width	(mm)	1756	1938	2008
Overall height	(mm)	2409	2484	
Wheelbase 2WD / 4WD	(mm)	2180 / 2132		