

TD5

		TD5.65	TD5.75	TD5.85	TD5.95	TD5.105	TD5.115
Engine name / Capacity / number of cylinders	(- / cm ³ / -)	S8000 / 2930 / 3		F5C / 3400 / 4			
Emission level		Tier 3 / Stage 3A		Tier 4A / Stage 3B			
Rated power	[kW/hp(CV)]	48/65	53/72	63/86	73/99	79/107	84/114
Maximum torque	(Nm)	261	295	351	407	444	457
Diesel tank capacity	(litres)	121					
Transmission type (1)		Synchro Command™ transmission					
Max. speed	(kph)	30					
Transmission type (2)		Synchro Shuttle™ transmission					
Max. speed	(kph)	30 / 40					
Transmission type (3)		Synchro Shuttle™ transmission with Creeper					
Max. speed	(kph)	30 / 40					
Transmission type (4)		Hydraulic Powershuttle transmission					
Max. speed	(kph)	30 / 40					
Maximum number of hydraulic remotes		3 rear remotes and 2 mid-mounts					
Maximum hydraulic flow	(lpm)	36		63			
Maximum rear lift capacity	(kg)	3000		3565	4700		
PTO Speeds		540, 540 or 540E, 540 or 1000, Ground speed					
Maximum permissible weight 2WD / 4WD	(kg)	5200 / 5400		- / 5800	5600 / 6000		- / 6500
Overall length including front support and rear linkage	(mm)	4200		4320			
Minimum width	(mm)	1920					
Overall height	(mm)	2590		2640	2665		2690
Wheelbase 2WD / 4WD	(mm)	2274 / 2224		- / 2280	2488 / 2280		- / 2280