

T7 STANDARD WHEELBASE

		T7.175	T7.190	T7.210	T7.225
Engine name / Capacity / number of cylinders	(- / cm ³ / -)	Nef / 6728 / 6			
Emissions level		Tier 4B / Stage 4			
Maximum engine power management power	[kW/hp(CV)]	129/175	140/190	154/210	165/225
Rated power	[kW/hp(CV)]	103/140	110/150	121/165	132/180
Maximum torque	(Nm)	750	805	875	940
Diesel tank capacity	(litres)	330			
Transmission type (1)		Range Command™ Semi-powershift		-	-
Max. Speed	(kph)	40		-	-
Transmission type (2)		Range Command™ Semi-powershift			-
Max. Speed	(kph)	40 ECO / 50			-
Transmission type (3)		Power Command™ Full Powershift			-
Max. Speed	(kph)	40			-
Transmission type (4)		Power Command™ Full Powershift			-
Max. Speed	(kph)	40 ECO / 50			-
Transmission type (5)		Auto Command™ Continuously Variable Transmission			
Max. Speed	(kph)	40 ECO			
Transmission type (6)		Auto Command™ Continuously Variable Transmission			
Max. Speed	(kph)	50 ECO			
Maximum number of hydraulic remotes		5 rear and 3 mid-mounts			
Maximum hydraulic flow	(lpm)	160			
Maximum rear lift capacity	(kg)	8257			
Maximum front linkage capacity	(kg)	3568			
PTO Speeds		540 or 1000, 540 or 540E or 1000, 540E or 1000 or 1000E			
Front PTO Speeds		1000			
Terraglide™ front axle suspension		optional			
Maximum permissible weight	(kg)	11,500			

		T7.175	T7.190	T7.210	T7.225
Overall length including weight pack and rear linkage	(mm)	5347			
Minimum width	(mm)	2446			
Overall height	(mm)	3040			
Wheelbase Standard axle / suspended axle / SuperSteer™ axle	(mm)	2734 / 2789 / 2880			