

**T8**

		T8.320	T8.350	T8.380	T8.410	T8.435
Engine name / Capacity / number of cylinders	( - / cm <sup>3</sup> / -)	FPT Cursor 9 / 8700 / 6				
Emissions level		Tier 4B / Stage 4				
Maximum engine power management power	[kW / hp(CV)]	235 / 320	258 / 351	281 / 381	301 / 409	320 / 435
Rated power	[kW / hp(CV)]	184 / 250	206 / 280	229 / 311	250 / 340	279 / 380
Maximum torque	(Nm)	1407	1558	1708	1800	1850
Diesel tank capacity Auto Command / Ultra Command / SmartTrax	(litres)	609 / 647 / -		609 / 647 / 670		609 / - / 670
Transmission type (1)		18 x 4 Ultra Command™ Full-Powershift				-
Max. speed		40				-
Transmission type (2)		19 x 4 Ultra Command™ Full-Powershift				-
Max. speed	(kph)	40 ECO / 50				-
Transmission type (3)		23 x 6 Ultra Command™ Full-Powershift with Creeper				-
Max. speed	(kph)	40				-
Transmission type (4)		Auto Command™ Continuously Variable Transmission				
Max. speed	(kph)	40				
Transmission type (5)		Auto Command™ Continuously Variable Transmission				
Max speed	(kph)	50				
Terraglide™ front axle suspension		optional				
Maximum number of hydraulic remotes		6				
Maximum hydraulic flow	(lpm)	279 / -		279 / 271		
Maximum rear lift capacity	(kg)	8843		9705	10.927	
Maximum front linkage capacity	(kg)	5810				
PTO Speeds		540 or 1000				
Front PTO Speeds		1000				
Maximum permissible weight - Wheeled T8/ T8 SmartTrax	(kg)	17,500 / -		17,500 / 20,000		

		T8.320	T8.350	T8.380	T8.410	T8.435
Overall length including weight pack and rear linkage	(mm)	6247				
Minimum width	(mm)	2534				
Overall height	(mm)	3338				
Wheelbase	(mm)	3500				