

### Braud 7030M and Braud 8030L

		BRAUD 7030M	BRAUD 8030L
Vineyard row spacing		Intermediate (>1.3m)	Large (>1.6m)
Engine name / Capacity / number of cylinders	( - / cm <sup>3</sup> / - )	FPT NEF / 4485 / 4	
Emissions level		Tier 4B/Stage 4	
Power ECE R120/ISO 14396	[kW/hp(CV)]	94/128	
Diesel capacity	(litres)	160	
Transmission		Heavy Duty Hydrostatic with Anti-Skid system	
Maximum speed	(kph)	25	
Maximum slope / lateral slope	(%)	32 / 25	
Blue Cab™ 4 system Pack: Featuring Category 4 filtration		Standard	Optional
Front multifunction tool carrier		Optional	
Harvesting head		With optional Destemmer and Opti-Grape™ system	
Number of SDC shakers		12	14
Sealed length of collection baskets / Number of baskets	(mm)	1900 / 2x54	2100 / 2x58
Stainless steel hoppers	(litres)	2300	2500/2800
High capacity cleaning conveyors	(mm)	450	600
New Holland Precision Land Management systems		Optional Row Tracking system GPS NH 162 (RTS) and hopper level indicator (progressive)	
Maximum length	(m)	5.03	5.17
Maximum width	(m)	2.61	2.77
Maximum height with cab, harvesting head on the ground	(m)	3.63	3.60
Ground clearance	(m)	1.80 to 2.30	1.95 to 2.45
Wheelbase	(m)	2.78	2.78