

COMPACT WHEEL LOADER

		W50C	W60C	W70C	W80C
Engine name / Capacity / number of cylinders	(- / cm ³ / -)	F5H / 3400 / 4			
Emissions level		Tier4B - Stage 4			
Maximum power	[kW/hp(CV)]	43/58	48/64	55/75	55/75
Maximum Torque	(Nm)	245	261	316	316
Diesel tank capacity	(litres)	87			
Transmission		Hydrostatic 4-wheel drive			
Maximum speed standard / optional (km/h)		20 / -	20 / -	20 / 33	20 / 33
Creeper		-	optional		
Maximum flow standard / optional	(lpm)	67 / -		85 / 130	
Maximum Tipping load straight with forks - Z-BAR / TC	(tonnes)	2.8 / 3.0	3.0 / 3.2	3.1 / -	3.6 / -
Maximum overall height with forks - Z-BAR / TC	(m)	3.48 / 3.63	3.53 / 3.65	3.63 / -	3.73 / -
Maximum reach with forks - Z-BAR / TC	(m)	1.35 / 1.26	1.41 / 1.27	1.43 / -	1.43 / -
Maximum Bucket volume Z-BAR / TC	(m ³)	1.0 / 1.0	1.1 / 1.1	1.2 / -	1.3 / -
Breakout force	(kgF)	6042 / 4104	5481 / 3925	6393 / -	6317 / -
Length with bucket	(m)	5.28 / 5.23	5.39 / 5.33	5.62 / -	5.68 / -
Maximum bucket height	(m)	3.14 / 3.94	3.18 / 4.09	3.29 / -	3.40 / -
Dig bucket depth	(mm)	730 / 130	120 / 140	100 / -	840 / -
Operating weight	(kg)	5020 / 4910	5160 / 4940	5559 / -	5910 / -
Height	(mm)	2460		2600	2680
width	(m)	1.90	2.05	2.05	2.10
Wheelbase	(m)	2.08		2.22	2.23