

BigBaler Large Square Baler

		BigBaler 870			BigBaler 890			BigBaler 1270		BigBaler 1290	
		Standard	Packer Cutter	CropCutter	Standard	Packer Cutter	CropCutter	Standard	CropCutter	Standard	CropCutter
Bale dimensions: Width / Height / Length (min - max)	(cm)	80 / 70 / 100 - 260			80 / 90 / 100 - 260			120 / 70 / 100 - 260		120 / 90 / 100 - 260	
Minimum tractor power requirements	[kW/hp(CV)]	75/102	80/110	95/130	75/102	80/110	95/130	85/114	105/141	90/122	110/150
PTO speed	(rpm)	1000									
Main Drive		Enclosed oil immersed triple reduction gearbox									
Pick-up width	(cm)	196						223	235	223	235
Feeding system		2 forks, 6 single tines	3 forks, 6 single tines	Rotor	2 forks, 6 single tines	3 forks, 6 single tines	Rotor	3 forks, 9 single tines	Rotor	3 forks, 9 single tines	Rotor
SmartFill™ system		Standard									
CropCutter™ System		-	Standard	-	Standard	-	Standard	-	Standard	-	Standard
Plunger speed / stroke length	(strokes/min / mm)	48 / 710									
Tying system		Double Knot									
Number of twines		4						6			
Twine ball capacity		32									
Bale density system		Proportional Three Way Control									
Electronic control system		ISO 11783 Connection Ready or optional IntelliView III or IntelliView IV monitors									
New Holland Precision Land Management systems		GPS data logging, bale weighing system									
Axles available		Single or tandem									
Length	(mm)	7477		7533	7477		7533	7477	7533	7477	7533
Width	(mm)	2398						2782			
Height	(mm)	3133		3223	3133		3223	3133	3223	3133	3223