

Profi


| MODEL | TRANSMISSION * | | | | ENGINE | | | | | | | PTO | | | | | | |
|--------------------|---------------------------------------------------|---------------------------------------------------|------------------------------------------------|------------------------------------|----------------------------------------------------------------------------------|----------------------------------------------------------------------|----------------------------|------------------------------------------------------------------------------------|----------------------------------------------------|-------------------------------------|-------------------------------------------|--------------------------------------|---------------------------------------------------------------------------------|--------------------------|------------------------------------------------------------------------------|---|------------------------|-----------------|
| | 2-stage Powershift with Powershuttle | 4-stage Powershift with Powershuttle | 4-stage Powershift with Powershuttle | Continuously Variable Transmission | Max. engine power ECE R120 ³⁾ Power Plus ¹⁾ * [kW (hp)] | Max. engine power ECE R120 ³⁾ @ 1,800/1,900 rpm [kW (hp)] | Nominal engine speed [rpm] | Max torque ECE R120 ³⁾ with Power Plus ¹⁾ * [Nm @ 1,500 rpm] | Max torque ECE R120 ³⁾ [Nm @ 1,500 rpm] | Torque rise Standard/Power Plus [%] | Engine capacity/Number of cylinders [cm3] | Fuel tank capacity diesel/AdBlue [l] | Common rail, 4-Cylinder diesel engine, turbo charged and intercooled / Stage 3B | | Common rail, 4-valve diesel engine, turbocharger with intercooler / stage 3B | | Ground speed PTO [rpm] | Front PTO [rpm] |
| | 24 forward and reverse gears | 16 forward and reverse gears | 17 forward and 16 reverse gears 40 kph Economy | 0-40 kph | | | | | | | | | PTO speed [rpm] | at engine speed of [rpm] | | | | |
| | 48 forward and reverse gears with creeper gearbox | 32 forward and reverse gears with creeper gearbox | 17 forward and 16 reverse gears 50 kph | 0-50 kph | | | | | | | | | 540/540E/1,000 or 540E/1,000/1,000E | 1,969/1,546 1,893 | 1,969/1,546/1,893 or 1,592/1,893/1,621 | | | |
| 4110 Profi CLASSIC | ■ — ○ | ○ — ○ | ○ — ○ | — — | 105/143 96/131 | 89/121 81/110 | 2,200 | 590 | 498 | 41/41 | 4,485 / 4 | 175/37 | ■ | — | ■ | — | O | O |
| 6125 Profi CLASSIC | ■ — ○ | ○ — ○ | ○ — ○ | — — | 121/165 111/151 | 101/137 92/125 | 2,200 | 682 | 566 | 42/41 | 6,728 / 6 | 227/37 | — | ■ | — | ■ | O | O |
| 6140 Profi CLASSIC | ■ — ○ | ○ — ○ | ○ — ○ | — — | 129/175 122/166 | 113/154 103/140 | 2,200 | 726 | 632 | 41/37 | 6,728 / 6 | 227/37 | — | ■ | — | ■ | O | O |
| 4110 Profi | — — | ■ — ○ | ○ — ○ | — — | 105/143 96/131 | 89/121 81 / 110 | 2,200 | 590 | 498 | 41/41 | 4,485 / 4 | 175/37 | ■ | — | ■ | — | O | O |
| 4120 Profi | — — | ■ — ○ | ○ — ○ | — — | 113/154 103/140 | 98/133 89/121 | 2,200 | 634 | 549 | 41/42 | 4,485 / 4 | 175/37 | ■ | — | ■ | — | O | O |
| 4130 Profi | — — | ■ — ○ | ○ — ○ | — — | 120/163 110/150 | 105/143 96/131 | 2,200 | 676 | 590 | 41/41 | 4,485 / 4 | 175/37 | — | ■ | — | ■ | O | O |
| 6125 Profi | — — | ■ — ○ | ○ — ○ | — — | 121/165 111/151 | 101/137 92/125 | 2,200 | 682 | 566 | 42/41 | 6,728 / 6 | 227/37 | — | ■ | — | ■ | O | O |
| 6140 Profi | — — | ■ — ○ | ○ — ○ | — — | 129/175 122/166 | 113/154 103/140 | 2,200 | 726 | 632 | 41/37 | 6,728 / 6 | 227/37 | — | ■ | — | ■ | O | O |
| 4110 Profi CVT | — — | — — | — — | ■ ○ | 105/143 96/131 | 89/121 81 / 110 | 2,200 | 590 | 498 | 41/41 | 4,485 / 4 | 175/37 | ■ | — | ■ | — | O | O |
| 4120 Profi CVT | — — | — — | — — | ■ ○ | 113/154 103/140 | 98/133 89/121 | 2,200 | 634 | 549 | 41/42 | 4,485 / 4 | 175/37 | ■ | — | ■ | — | O | O |

| | | | | | | | | | | | | | | | | | |
|----------------------|--------|--------|--------|--------|--------------------|-------------------|-------|-----|-----|-------|-----------|--------|---|--------|--------|---|---|
| 4130 Profi CVT | - - | - - | - - | - O | 120/163 110/150 | 105/143 96/131 | 2,200 | 676 | 590 | 41/41 | 4,485 / 4 | 175/37 | - | - ■ | - ■ | O | O |
|----------------------|--------|--------|--------|--------|--------------------|-------------------|-------|-----|-----|-------|-----------|--------|---|--------|--------|---|---|

| MODEL | HYDRAULICS | | | | | | | | | | 4WD and steering | | TYRES | WEIGHT WITH CAB AND 4WD | STEYR SK3 CAB |
|--------------------------|------------------------------------------------------------------------------------------------|-----------------------------------|--------------------------------------------------------------------|----------------------------------------------------------------|---------------------------------------------------------------------|---------------------------------------------------|------------|-----------------------|-----------------------|--------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------|-------------------------------------------------------------------|-----------------------------------------|-----------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | EHR control (electronic hitch regulation) with oscillation cancelling Ride Control | Max. capacity | | | Max. lift capacity 80 l/113 l displacement rating [kg] | Up to 4 freely- configurable 1 power beyond | | valves | | Integrated front hitch* Max. lift capacity at 80/113 l/min Displacement rating [kg] | Electro-hydraulic 4WD engagement with traction management | steering lock angle [°] turning radius [km] | Standard tyres* front rear | Weight empty [kg]/ permissible total weight [kg] | |
| | | 80 l/min with constant pump | 113 l/min with pressure/ flow control, load sensing | 125 l/min with pressure/flow control, load sensing | | mechanical | electrical | up to 2 mechanical | up to 3 electrical | | | | | | |
| 4110 Profi CLASSIC | ■ | ■ | O | - | 7,115 / 7,864 | ■ | - | ■ | - | 2,800/3,100 | ■ | 55° 4.04 | 440/65R28 540/65R38 | 4,890/9,500 | Version with low roof, access steps on both sides, spacious, unrestricted entry, noise level inside cab: 73 dB(A), air suspension seat, air conditioning, interior lighting, tinted glass, opening rear window, wash/wipe system, front and rear work lights on cab roof, control panel for work lights |
| 6125 Profi CLASSIC | ■ | ■ | O | - | 7,115 / 7,864 | ■ | - | ■ | - | 2,800/3,100 | ■ | 55° 4.36 | 440/65R28 540/65R38 | 5,010/9,500 | |
| 6140 Profi CLASSIC | ■ | ■ | O | - | 7,115 / 7,864 | ■ | - | ■ | - | 2,800/3,100 | ■ | 55° 4.36 | 440/65R28 540/65R38 | 5,020/9,500 | |
| 4110 Profi | ■ | - | ■ | - | 7.864 | - | ■ | - | ■ | -/3,100 | ■ | 55° 4.04 | 480/65R28 600/65R38 | 4,890/9,500 | |
| 4120 Profi | ■ | - | ■ | - | 7.864 | - | ■ | - | ■ | -/3,100 | ■ | 55° 4.04 | 480/65R28 600/65R38 | 4,890/9,500 | |

| | | | | | | | | | | | | | | | |
|-----------------------|---|---|---|---|-------|---|---|---|---|----------|---|-------------|------------------------|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 4130 Profi | ■ | - | ■ | - | 7.864 | - | ■ | - | ■ | -/3,100 | ■ | 55° 4.04 | 480/65R28 600/65R38 | 4,890/9,500 | wash/wipe system, front and rear work lights in cab roof, central control panel for work lights, Multicontroller armrest with Multicontroller, intuitive control panel and Steyr joystick*), performance monitor optional: cab suspension, telescopic rear view mirrors, 2/4 working lights, rear window wash/wipe system |
| 6125 Profi | ■ | - | ■ | - | 7.864 | - | ■ | - | ■ | -/3,100 | ■ | 55° 4.36 | 480/65R28 600/65R38 | 5,010/9,500 | Multicontroller, intuitive control panel and Steyr joystick*), performance monitor optional: cab suspension, telescopic rear view mirrors, 2/4 working lights, rear window wash/wipe system |
| 6140 Profi | ■ | - | ■ | - | 7.864 | - | ■ | - | ■ | -/3,100 | ■ | 55° 4.36 | 480/65R28 600/65R38 | 5,020/9,500 | Access steps on both sides, spacious, unrestricted entrance to cab, noise level inside: 69 dB(A), air-suspension seat, air conditioning, interior lighting, 90° pivoting windscreen, tinted glass and rear window that can be opened, wash/wipe system, front and rear work lights in cab roof, central control panel for work lights, Multicontroller armrest with Multicontroller, intuitive control panel and Steyr joystick*), performance monitor optional: cab suspension, telescopic rear view mirrors, 2/4 working lights, rear window wash/wipe system |
| 4110 Profi CVT | ■ | - | - | ■ | 7.864 | - | ■ | - | ■ | -/-3,100 | ■ | 55° 4.04 | 480/65R28 600/65R38 | 4,990/9,500 | air-suspension seat, air conditioning, interior lighting, 90° pivoting windscreen, tinted glass and rear window that can be opened, wash/wipe system, front and rear work lights in cab roof, central control panel for work lights, Multicontroller armrest with Multicontroller, intuitive control panel and Steyr joystick*), performance monitor optional: cab suspension, telescopic rear view mirrors, 2/4 working lights, rear window wash/wipe system |
| 4120 Profi CVT | ■ | - | - | ■ | 7.864 | - | ■ | - | ■ | -/-3,100 | ■ | 55° 4.04 | 480/65R28 600/65R38 | 4,990/9,500 | wash/wipe system, front and rear work lights in cab roof, central control panel for work lights, Multicontroller armrest with Multicontroller, intuitive control panel and Steyr joystick*), performance monitor optional: cab suspension, telescopic rear view mirrors, 2/4 working lights, rear window wash/wipe system |
| 4130 Profi CVT | ■ | - | - | ■ | 7.864 | - | ■ | - | ■ | -/-3,100 | ■ | 55° 4.04 | 480/65R28 600/65R38 | 4,990/9,500 | wash/wipe system, front and rear work lights in cab roof, central control panel for work lights, Multicontroller armrest with Multicontroller, intuitive control panel and Steyr joystick*), performance monitor optional: cab suspension, telescopic rear view mirrors, 2/4 working lights, rear window wash/wipe system |

■ Standard ○ Optional – not available

¹⁾ Power Plus is enabled if certain conditions apply during transport, hydraulic and PTO work. ²⁾ With standard tyres

³⁾ ECE R120 complies with ISO 14396 or 2000/25/EC or EG 97/68 *) Depending on country-specific legislation and specifications
