

### Farmall C

		Farmall 55 C	Farmall 65 C	Farmall 75 C	Farmall 85 C	Farmall 95 C	Farmall 105 C	Farmall 115 C
Engine name / size / number of cylinders	( - / cm <sup>3</sup> / -)	F5C /3,400 / 4						
Emissions level		Tier 4A / Stage IIIB						
Rated power	(hp[CV])	58	65	75	86	99	107	114
Maximum torque	(Nm)	244	275	309	351	407	444	457
Diesel tank capacity	(litres)	90			115			
Transmission type (1)		12 x 12 Synchroshift with mechanical shuttle						
Max. Speed	(kph)	40						
Transmission type (2)		12 x 12 Synchroshift with PowerShuttle						
Max. Speed	(kph)	40						
Transmission type (3)		20 x 20 Synchroshift with mechanical shuttle and creeper						
Max. Speed	(kph)	40						
Transmission type (4)		20 x 20 Synchroshift with power shuttle and creeper						
Max. Speed	(kph)	40						
Transmission type (5)		-			24 x 24 two speed powershift with PowerShuttle			
Max. Speed	(kph)	-			40			
Transmission type (6)		-			40x 40 two speed powershift with power shuttle with creeper			
Max. Speed	(kph)	-			40			
Maximum number of hydraulic remotes		3 mechanical and two mechanical mid-mounts						
Maximum hydraulic flow	(Litres/minute)	84			100			
Maximum rear lift capacity	(kg)	2,500			3,700			
PTO Speeds		540, 540E (ground speed optional)			540, 540E or 540, 1000 (ground speed optional)			
Maximum permissible weight	(kg)	4,500			6,000			

		Farmall 55 C	Farmall 65 C	Farmall 75 C	Farmall 85 C	Farmall 95 C	Farmall 105 C	Farmall 115 C
Overall length including weight pack and rear linkage	(mm)	4,001			4,243			
Minimum width	(mm)	1,922			1,923			
Overall height	(mm)	2,378	2,423		2,490		2,537	
Wheelbase	(mm)	2,102			2,235			