

MODEL	Nutri-Placer 5300, 22.5 Ft.	Nutri-Placer 5300, 27.5 Ft.	Nutri-Placer 5300, 32.5 Ft.	Nutri-Placer 5300, 37.5 Ft.
Working Width, ft	23	28	33	38
Ground engagement, Strip-Till or other	Shank-based insertion	Shank-based insertion	Shank-based insertion	Shank-based insertion
Fertilizer material: Dry, Liquid, or Anhydrous	Anhydrous	Anhydrous	Anhydrous	Anhydrous
Working width, ft-in (m)	22' 6" (6.9)	27' 6" (8.4)	32' 6" (9.9)	37' 6" (11.4)
Number of rows	up to 18 rows @ 15"	up to 22 rows @ 15"	up to 26 rows @ 15"	up to 30 rows @ 15"
Row spacings, in (mm)	Various, 15 to 40 (381 to 1016)	Various, 15 to 40 (381 to 1016)	Various, 15 to 40 (381 to 1016)	Various, 15 to 40 (381 to 1016)
Hookup to tractor, Mounted or Pull-type	3-point mounted	3-point mounted	3-point mounted	3-point mounted
Coulter diameter, in (mm)	20 or 24 (508 or 610)	20 or 24 (508 or 610)	20 or 24 (508 or 610)	20 or 24 (508 or 610)
Shanks/knives	Rigid or trip shank w/ two-bolt side knife	Rigid or trip shank w/ two-bolt side knife	Rigid or trip shank w/ two-bolt side knife	Rigid or trip shank w/ two-bolt side knife
Sealing discs, closing discs, berm builder, in (mm)	14 or 18 (356 or 457) smooth or notched	14 or 18 (356 or 457) smooth or notched	14 or 18 (356 or 457) smooth or notched	14 or 18 (356 or 457) smooth or notched
Toolbar rigid or flexible	3 Section flex	3 Section flex	3 Section flex	3 Section flex
Depth adjustment	Pin-adjust gauge wheels	Pin-adjust gauge wheels	Pin-adjust gauge wheels	Pin-adjust gauge wheels
Power needed, hp (kW)	150 to 200 (112 to 149)	165 to 220 (123 to 164)	195 to 260 (145 to 194)	225 to 300 (168 to 224)