

MODEL	Maxxum 115 MultiController	Maxxum 125 MultiController	Maxxum 135 MultiController	Maxxum 145 MultiController	Maxxum 150 MultiController
Displacement, cu in (L) / No. of Cylinders	274 (4.5) / 4	274 (4.5) / 4	274 (4.5) / 4	274 (4.5) / 4	411 (6.7) / 6
Rated power (hp)	114hp @ 2200rpm	123hp @ 2200rpm	133hp @ 2200rpm	143hp @ 2200rpm	143hp @ 2200rpm
Maximum Engine Power (hp)	145	155	169	175	175
Power Boost, hp	29	34	32	30	30
PTO Horsepower with standard options hp	95	105	110	120	125
PTO Speeds, rpm	540 / 1000	540 / 1000	540 / 1000	540 / 1000	540 / 1000
Aspiration, Turbocharged or Naturally Aspirated	Turbocharged w/ Air-to-Air Intercooler	Turbocharged w/ Air-to-Air Intercooler	Turbocharged w/ Air-to-Air Intercooler	Turbocharged w/ Air-to-Air Intercooler	Turbocharged w/ air-to-air Intercooler
Standard transmission configuration	16x16 Semi-Powershift	16x16 Semi-Powershift	16x16 Semi-Powershift	16x16 Semi-Powershift	16x16 Semi-Powershift
Maximum Speed Forward, mph (kph)	25 (40)	25 (40)	25 (40)	25 (40)	25 (40)
Creeper Range Available	Optional	Optional	Optional	Optional	Optional
Transmission option 1	17x16 Semi-Powershift (25 or 30 mph)	17x16 Semi-Powershift (25 or 30 mph)	17x16 Semi-Powershift (25 or 30 mph)	17x16 Semi-Powershift (25 or 30 mph)	17x16 Semi-Powershift (25 mph)
Transmission option 2	CVT, 25 or 31 mph	CVT, 25 or 31 mph	CVT, 25 or 31 mph	CVT, 25 or 31 mph	17x16 Semi-Powershift (30 mph)
Hydraulic System Type	Pressure Flow Compensated	Pressure Flow Compensated	Pressure Flow Compensated	Pressure Flow Compensated	Pressure Flow Compensated
Standard flow, gpm (Lpm)	29.8 (113)	29.8 (113)	29.8 (113)	29.8 (113)	29.8 (113)

MODEL	Maxxum 115 MultiController	Maxxum 125 MultiController	Maxxum 135 MultiController	Maxxum 145 MultiController	Maxxum 150 MultiController
Number of Standard Remote Valves	3 std; 4 opt	3 std; 4 opt	3 std; 4 opt	3 std; 4 opt	3 std; 4 opt
Maximum Lift Capacity 24 Inches behind pin, lb (kg)	7,700 (3492) OECD	7,700 (3492) OECD	7,700 (3492) OECD	7,700 (3492) OECD	7,700 (3492) OECD
Wheelbase in (mm)	104 (2642) std; 106.2 (2697) opt. susp. front	104 (2642) std; 106.2 (2697) opt. susp. front	104 (2642) std; 106.2 (2697) opt. susp. front	104 (2642) std; 106.2 (2697) opt. susp. front	104 (2642) std; 106.2 (2697) opt. susp. front
Overall length , in (mm)	175.8 (4465) std.;; 178 (4520) Suspended	175.8 (4465) std.;; 178 (4520) Suspended	175.8 (4465) std.;; 178 (4520) Suspended	175.8 (4465) std.;; 178 (4520) Suspended	175.8 (4465) std.;; 178 (4520) Suspended
Height to Top of Cab/ROPS for non cabbed versions, in (mm)	84.6 (2150)	84.6 (2150)	84.6 (2150)	84.6 (2150)	84.6 (2150)
Overall Width, with standard wheels or tracks, in (mm)	98 (2489) Bar axle ends	98 (2489) Bar axle ends	98 (2489) Bar axle ends	98 (2489) Bar axle ends	98 (2489) bar axle ends
Overall Weight without ballast, lb (kg)	11,300 (5125)	11,300 (5125)	11,300 (5125)	12,500 (5670)	12,800 (5806)