

## CX Combines



Specification Item		CX8.80	CX8.90
Min. / Max. cutting width grain header	(ft)	20/35	20/41
Min. / Max. number of rows corn header		6/12*	6/12*
Monitor options		YES	YES
Optimum cab noise level	(dB(A))	73	73
Guidance systems		YES	YES
Precision Farming systems		YES	YES
Threshing drum width / diameter / number of bars / speed range	(in / in / - /rpm)	62/30/10/305-905	62/30/10/305-905
Drum concave area / number of bars / wrap angle	(in / - / °)	1829/16/111	1829/16/111
Beater diameter / concave area	(in / in <sup>2</sup> )	19 / 450	19 / 450
Rotary separator diameter / speed / concave area	(ft / rpm / ft <sup>2</sup> )	28/387/1441	28/387/1441
Number of strawwalkers / separation area	(- / ft <sup>2</sup> )	6	6
Cleaning: total area under wind control	(in <sup>2</sup> )	10,075	10,075
Cleaning fan		Opti-Fan	Opti-Fan
Grain tank capacity	(bu)	350	355
Unloading speed	(bu/min)	3.5	3.5
Engine capacity	(in <sup>3</sup> )	3425	4066
Gross engine power	(hp)	360	449
Max. engine power	(hp)	401	490
Fuel tank capacity	(gallons)	265	265
Transmission		4 Speed Hydrostatic	4 Speed Hydrostatic
Residue management			
Standard version less header	(lb)	34225	35349
Maximum height	(ft)	13	13
Maximum width	(ft)	12.4	12.4
Maximum length	(ft)	29.7	29.7

\*Only 12 row non chopping corn heads