



|                                       | CM109                          | CM209                          | CM212                          |
|---------------------------------------|--------------------------------|--------------------------------|--------------------------------|
| <b>DIMENSIONS</b>                     |                                |                                |                                |
| Transport Width                       | 172 in. (4.4 m)                | 172 in. (4.4 m)                | 184 in. (4.7 m)                |
| Transport Length                      | 231 in. (5.9 m)                | 264 in. (6.7 m)                | 264 in. (6.7 m)                |
| Transport Height                      | 54 in. (1.4 m)                 | 63 in. (1.6 m)                 | 63 in. (1.6 m)                 |
| <b>WEIGHT</b>                         |                                |                                |                                |
| Base Unit - Tractor Hydraulics        | 2880 lbs. (1306 kg)            | 3320 lbs. (1505 kg)            | 3860 lbs. (1751 kg)            |
| Base Unit - Self-Contained Hydraulics | 3380 lbs. (1533 kg)            | 3780 lbs. (1714 kg)            | 4320 lbs. (1960 kg)            |
| <b>PICKUP</b>                         |                                |                                |                                |
| Width                                 | 108 in. (2.7 m)                | 108 in. (2.7 m)                | 144 in. (3.7 m)                |
| Type                                  | Spliced Belt w/Plastic Fingers | Spliced Belt w/Plastic Fingers | Spliced Belt w/Plastic Fingers |
| Pickup Tooth Type                     | Replaceable 3 Prong, Plastic   | Replaceable 3 Prong, Plastic   | Replaceable 3 Prong, Plastic   |
| Separate Belt Sections                | 3 x 3 ft. (0.9 x 0.9 m)        | 3 x 3 ft. (0.9 x 0.9 m)        | 4 x 3 ft. (1.2 x 0.9 m)        |
| Adjustable Pickup and Conveyor Speed  |                                |                                |                                |
| Tractor Driven                        | Tractor Remote Flow Control    | Tractor Remote Flow Control    | Tractor Remote Flow Control    |
| Self-Contained                        | Tractor PTO Speed              | Tractor PTO Speed              | Tractor PTO Speed              |
| Floating Pickup                       | Standard, On Gauge Wheels      | Standard, On Gauge Wheels      | Standard, On Gauge Wheels      |
| Lift System                           | Hydraulic                      | Hydraulic                      | Hydraulic                      |
| Drive Type                            | Hydraulic                      | Hydraulic                      | Hydraulic                      |
| Roller Windguard                      | N/A                            | Standard                       | Standard                       |
| <b>CROSS CONVEYOR</b>                 |                                |                                |                                |
| Width                                 | 42 in. (1.1 m)                 | 42 in. (1.1 m)                 | 42 in. (1.1 m)                 |
| Length                                | 170.8 in. (4.3 m)              | 175.5 in. (4.5 m)              | 175.5 in. (4.5 m)              |
| Drive Type                            | Hydraulic                      | Hydraulic                      | Hydraulic                      |
| Belt Type                             | Spliced                        | Spliced                        | Spliced                        |
| Discharge Side                        | Right (Left to Invert Only)    | Right (Left to Invert Only)    | Right (Left to Invert Only)    |
| <b>MERGING CAPABILITY</b>             |                                |                                |                                |
| Width of cut, Base Unit               | 9 to 12 ft. (2.7 to 3.7 m)     | 9 to 12 ft. (2.7 to 3.7 m)     | 9 to 12 ft. (2.7 to 3.7 m)     |
| Width of cut, 2 ft. (0.6 m) Extension | 11 to 14 ft. (3.4 to 4.3 m)    | 9 to 14 ft. (2.7 to 4.3 m)     | 9 to 14 ft. (2.7 to 4.3 m)     |
| Width of cut, 4 ft. (1.2 m) Extension | N/A                            | 9 to 16 ft. (2.7 to 4.9 m)     | 9 to 16 ft. (2.7 to 4.9 m)     |
| Width of cut, 6 ft. (1.8 m) Extension | N/A                            | 9 to 18 ft. (2.7 to 5.5 m)     | 9 to 18 ft. (2.7 to 5.5 m)     |
| <b>FRAME AND TONGUE</b>               |                                |                                |                                |
| Type Pull                             | Center                         | Side                           | Side                           |
| Tongue Swing                          | N/A                            | Hydraulic                      | Hydraulic                      |
| Ground Clearance - Pickup Raised      | 10 in. (254 mm)                | 11.75 in. (298 mm)             | 11.75 in. (298 mm)             |
| Recommended Operating Speeds          | 2 to 12 mph (3.2 to 19.3 k/h)  | 2 to 12 mph (3.2 to 19.3 k/h)  | 2 to 12 mph (3.2 to 19.3 k/h)  |
| Maximum Transport Speed               | 30 mph (32 k/h)                | 30 mph (32 k/h)                | 30 mph (32 k/h)                |
| Wheels and Tires (# of tires)         | {3} 6.70 x 15                  | {1} 6.70 x 15, {2} 9.5L x 15   | {1} 6.70 x 15, {2} 9.5L x 15   |

| <b>TRACTOR REQUIREMENTS</b>        |   |
|------------------------------------|---|
| <b>Hydraulic Flow Requirements</b> |   |
| With Tractor Hydraulics            | 16 gpm @ 2000 psi (61 lpm @ 138 bar)            |
| With Self-Contained Hydraulics     | 5 gpm @ 2000 psi (19 lpm @ 138 bar)             |
| Hydraulic Remotes Required         | 2 w/Tractor Driven, 1 w/Self-Contained          |
| <b>Hydraulic Remote Valve Type</b> |   |
| With Tractor Hydraulics            | Double Acting with Detent and Flow Control on 1 |
| With Self-Contained Hydraulics     | Single or Double Acting                         |
| Minimum Tractor HP Recommended     | 70 HP (52 kW)                                   |
| Seven Pin Light Connector          | Required  |

| <b>STANDARD EQUIPMENT</b> |  |
|---------------------------|--|
| Clevis Hitch              |  |
| Parking Jack              |  |
| Pickup Gauge Wheels       |  |
| Transport Lock for Pickup |  |
| Transport Chain           |  |
| SMV Emblem                |  |

| <b>OPTIONAL EQUIPMENT</b>         |  |
|-----------------------------------|--|
| <b>CM109</b>                      |  |
| Windrow Inverter Attachment       |  |
| 2 ft. Conveyor Extension          |  |
| <b>CM209 and CM212</b>            |  |
| Windrow Inverter Attachment       |  |
| 2 ft. Conveyor Extension          |  |
| 4 ft. Conveyor Extension          |  |
| 6 ft. Conveyor Extension          |  |
| Cross Conveyor Extension Shut-off |  |



**Safety Never Hurts!™** Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided.

CNH America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice.

Case IH is a registered trademark of CNH America LLC.

Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies.

Availability of some models and equipment builds vary according to the country in which the equipment is used.