

Magnum CVX

		Magnum 250 CVX	Magnum 280 CVX	Magnum 310 CVX and Magnum 310 Rowtrac CVX	Magnum 340 CVX and Magnum 340 Rowtrac CVX	Magnum 380 CVX and Magnum 380 Rowtrac CVX
Engine name / size / number of cylinders	(- / cm ³ / -)	Cursor 9 / 8,700 / 6				
Emissions level		Tier 4B, Stage IV				
Maximum engine power management power	(hp[CV])	320	351	382	409	435
Maximum power	(hp[CV])	284	315	347	374	417
Rated power	(hp[CV])	250	280	311	340	379
Maximum torque	(Nm)	1,229	1,381	1,531	1,671	1,850
Diesel tank capacity	(litres)	617				
Transmission type (1)		Continuously variable transmission with power shuttle				
Min. / max. speed	(kph)	50				
Maximum number of hydraulic remotes		6 electronic				
Maximum hydraulic flow	(Litres/minute)	282				
Maximum rear lift capacity	(kg)	8,843		9,705		10,927
Maximum front linkage capacity	(kg)	5,000				
PTO Speeds		540 , 1000				
Front axle suspension		Optional				

		Magnum 250 CVX	Magnum 280 CVX	Magnum 310 CVX	Magnum 340 CVX	Magnum 380 CVX
Maximum permissible weight	(kg)	17,530	17,850		18,000	
Overall length including weight pack and rear linkage	(mm)	6,295			6,575	
Minimum width	(mm)	2,550				
Overall height	(mm)	3,375				
Wheelbase	(mm)	3,105			3,155	

		Magnum 310 CVX Rowtrac	Magnum 340 CVX Rowtrac	Magnum 380 CVX Rowtrac
Shipping weight	(kg)	17,113		
Overall length including weight pack and rear linkage	(mm)	6,295		
Minimum width	(mm)	2,540	2,650	
Overall height	(mm)	3,450		
Wheelbase	(mm)	3,155		