

T3F

		T3.50F	T3.55F	T3.65F	T3.75F
Engine name / Capacity / number of cylinders	(- / cm ³ / -)	S8000 Series / 2930 / 3			
Emissions level		Tier 3 / Stage 3A			
Rated power	[kW/hp(CV)]	36.8/50	40.4/55	47.8/65	53/72
Maximum torque	(Nm)	201	220	261	295
Diesel tank capacity	(litres)	50			
Transmission type (1)		12x12 30 kph- Mech Shuttle			
Max. Speed	(kph)	30			
Transmission type (2)		20x20 (12x12 creeper version) Mech Shuttle			
Max. Speed	(kph)	30			
Transmission type (3)		12x12 Mech Shuttle			
Max. Speed	(kph)	40			
Transmission type (4)		20x20 (12x12 creeper version) Mech Shuttle			
Max. Speed	(kph)	40			
Maximum number of hydraulic remotes		3			
Maximum hydraulic flow	(lpm)	52			
Maximum rear lift capacity	(kg)	2277			
PTO Speeds		540 or 540E			
Maximum permissible weight	(kg)	2200			
Overall length	(mm)	3438			
Minimum width	(mm)	1350			
Overall height	(mm)	2246			
Wheelbase	(mm)	1863			