

T4

| | | T4.75 | T4.85 | T4.95 | T4.105 | T4.115 |
|---|----------------------------|--|-------|-------|--------|--|
| Engine name / Capacity / number of cylinders | (- / cm ³ / -) | F5C / 3400 / 4 | | | | |
| Emissions level | | Tier 4A / Stage 3B | | | | |
| Rated power | [kW/hp(CV)] | 55/75 | 63/86 | 73/99 | 79/107 | 84/114 |
| Maximum torque | (Nm) | 309 | 351 | 407 | 444 | 457 |
| Diesel tank capacity | (litres) | 115 | | | | |
| Transmission type (1) | | Synchro Shuttle™ transmission | | | | |
| Max. Speed | (kph) | 30 / 40 | | | | |
| Transmission type (2) | | Synchro Shuttle™ transmission with creeper | | | | |
| Max. Speed | (kph) | 30 / 40 | | | | |
| Transmission type (3) | | Hydraulic Powershuttle transmission | | | | |
| Max. Speed | (kph) | 30 / 40 | | | | |
| Transmission type (4) | | Hydraulic Powershuttle transmission with creeper | | | | |
| Max. Speed | (kph) | 30 / 40 | | | | |
| Transmission type (5) | | Split Command™ transmission | | | | |
| Max. Speed | (kph) | 30 / 40 | | | | |
| Transmission type (6) | | Dual Command™ transmission | | | | |
| Max. Speed | (kph) | 40 | | | | |
| Transmission type (7) | | Dual Command™ transmission with creeper | | | | |
| Max. Speed | (kph) | 40 | | | | |
| Maximum number of hydraulic remotes | | 3 rear and two mid-mounts | | | | |
| Maximum hydraulic flow | (lpm) | 64 | | | | |
| Maximum rear lift capacity | (kg) | 3884 | | | | |
| Maximum front linkage capacity | (kg) | 1670 | | | | |
| PTO Speeds | | 540, 540 or 540E, 540 or 1000, 540E or 1000 | | | | 540 or 540E, 540 or 1000, 540E or 1000 |
| Maximum permissible weight | (kg) | 6000 | | | | |
| Overall length including front support and rear linkage | (mm) | 4036 | | | | |

| | | T4.75 | T4.85 | T4.95 | T4.105 | T4.115 |
|---|------|-------------|-------|-------|--------|--------|
| Minimum width | (mm) | 1953 | | | | |
| Overall height | (mm) | 2519 | | | | |
| Wheelbase (2WD front axle / 4WD front axle) | (mm) | 2293 / 2235 | | | | |