

### T4LP

		T4.75 LP	T4.85 LP	T4.95 LP	T4.105 LP
Engine name / Capacity / number of cylinders	(- / cm <sup>3</sup> / -)	F5C / 3200 / 4	F5C / 3200 / 4	NEF / 4500 / 4	NEF / 4500 / 4
Emissions level		Tier 3 / Stage 3A			
Rated power	[kW/hp(CV)]	57/78	65/88	71/97	78/106
Maximum torque	(Nm)	330	352	398	425
Diesel tank capacity	(litres)	98			
Transmission type (1)		16 x 16 Shuttle Command™			
Max. Speed	(kph)	30 / 40			
Transmission type (2)		28 x 16 Shuttle Command™ with Creeper			
Max. Speed	(kph)	30 / 40			
Transmission type (3)		32 x 16 Split Command™			
Max. Speed	(kph)	30 / 40			
Transmission type (4)		16 x 16 Powershuttle			
Max. Speed	(kph)	30 / 40			
Transmission type (5)		32 x 16 Dual Command™ and parking lock			
Max. Speed	(kph)	30 / 40			
Transmission type (5)		44 x 16 Dual Command™ with Creeper and parking lock			
Max. Speed	(kph)	30 / 40			
Maximum number of hydraulic remotes		5 rear and 4+1 mid-mounts			
Maximum hydraulic flow	(lpm)	63.8			
Maximum rear lift capacity	(kg)	2600			
PTO Speeds		540, 540 or 540E, 540 or 540E or 1000			
Weights ROPS / CAB	(kg)	2800 / 3010	2800 / 3010	2800 / 3010	2800 / 3010
Overall length	(mm)	3942		4029	
Minimum width	(mm)	1588		1588	
Overall height ROPS / cab	(mm)	2274 / 2173		2360 / 2173	
Wheelbase	(mm)	2093		2180	