

**CX7 and CX8 Combine**

		CX7.80	CX7.90	CX8.70	CX8.80	CX8.85	CX8.90	
Min. / Max. cutting width grain header	(m)	4.57 - 7.32		5.18 - 9.15	6.10 - 10.67	7.32 - 10.67		
Min. / Max. number of rows maize header		6	6 - 8		6 - 8 - 12			
New Holland Precision Land Management systems		Optionals						
Threshing drums Width / Diameter	(m)	1.3 / 0.75		1.56 / 0.75				
Sectional Concaves Area	(m <sup>2</sup> )	0.98		1.18				
Rotary Separator		Standard						
Total powered separation area	(m <sup>2</sup> )	2.11		2.54				
Strawwalkers Number		5		6				
Cleaning: Total sieve area under wind control	(m <sup>2</sup> )	5.4		6.5				
Opti-Fan™ system		Standard						
Graintank capacity	(litres)	9000	10,000	11,500		12,500		
Engine name / Capacity	( - / cm <sup>3</sup> )	FPT Cursor 9 / 8700						FPT Cursor 10 / 10300
Emissions level		Tier 4B/Stage 4						Tier 4A/Stage 3B
Maximum power	[kW/hp(CV)]	250/340	275/374	275/374	295/401	330/449	360/490	
Diesel tank capacity	(litres)	750			1000			
Transmission		4-speed Hydrostatic Gearbox						
SmartTrax™ system / SmartTrax™ with Terraglide™ suspension		- / -	Optional / Optional	- / -	Optional / Optional			
Residue management		Optional Opti-Spread™ system						
Weight	(kg)	14,266	14,802	15,507	15,538	16,034		
Maximum length without header	(m)	9.07						
Min width in transport position	(m)	3.2		3.69				
Max height in transport position	(m)	3.96						