

TC Combine Range

		TC4.90	TC5.70	TC5.80	TC5.90
Min. / Max. cutting width grain header	(m)	3.96 - 5.18		3.96 - 6.10	
Number of rows maize header		5		5 / 6	
Optimum cab noise level	(dB(A))	74			
Threshing drum width / diameter	(m / m)	1.04 / 0.607	1.30 / 0.607		
Drum concave area	(m ²)	0.63	0.79		
Rotary separator diameter /concave area	(m / m ²)	0.605 / 0.66	0.605 / 0.83		
Number of strawwalkers / separation area	(- / m ²)	4 / 4.41	5 / 5.51		
Cleaning: total area under sieve control	(m ²)	3.44	4.3		
Cleaning fan		Opti-Fan optional			
Grain tank capacity	(litres)	5000	5200	6400	
Unloading speed	(litres/s)	72			
Engine name / Capacity	(- / cm ³)	NEF / 6800			
Emissions level		Tier 4A / Stage 3B			
Max. engine power	[kW/hp(CV)]	175		227	258
Gross engine power	[kW/hp(CV)]	170		211	238
Diesel tank capacity	(litres)	300	400		
Transmission		Three-speed hydrostatic Gearbox			
Residue management		Dual-Chop system			
Weight Standard version less header	(kg)	8850	9150	10,700	10,750
Maximum length	(mm)	8298			
Minimum width	(mm)	2943	3146	3267	