

CX5000 and CX6000 Elevation Combine Range

		CX5080 Elevation	CX5090 Elevation	CX6080 Elevation	CX6090 Elevation
Min. / Max. cutting width grain header	(m)	4.57 - 7.32		4.57 - 9.15	4.88 - 9.15
Number of rows maize header		5 / 6 / 8		6 / 8	
Monitor options		IntelliView IV colour touchscreen monitor			
Optimum cab noise level	(dB(A))	76			
Guidance systems		Optional SmartSteer			
New Holland Precision Land Management systems		Yield and Moisture monitoring optional			
Threshing drum width / diameter	(m / m)	1.3 / 0.6		1.56 / 0.6	
Drum concave area	(m ²)	0.86		1.04	
Beater diameter / concave area	(m / m ²)	0.395 / 0.286		0.395 / 0.342	
Rotary separator diameter / concave area	(m / m ²)	0.59 / 0.84		0.59 / 1.01	
Number of strawwalkers / separation area	(- / m ²)	5 / 5.38		6 / 6.45	
Cleaning: total area under sieve control	(m ²)	4321		5207	
Cleaning fan		Standard Opti-Fan System			
Grain tank capacity	(litres)	8300		9300	
Unloading speed	(litres/s)	90	100		
Engine name / Capacity	(- / cm ³)	NEF / 6700			Cursor 9 / 8700
Emissions level		Tier 4A / Stage 3B			
Max. engine power	[kW/hp(CV)]	190/258	220/300		245/333
Gross engine power	[kW/hp(CV)]	175/238	200/272		220/300
Diesel tank capacity	(litres)	670			
Transmission		Three-speed hydrostatic Gearbox			
Maximum speed	(kph)	30			
Residue management		Optional Dual-Chop system			
Weight Standard version less header and less straw chopper	(kg)	12,300	12,400	13,200	13,400
Maximum length	(mm)	8760			
Maximum width	(mm)	3275	3265	3500	
Maximum height	(mm)	3930	3990		
Optional Laterale Version		-	Available option	-	Available option
Optional Hillside Narrow Version		-	Available option	-	
Optional Hillside Wide Version		-	Available option	-	