

TK4000

		TK4020V	TK4020F	TK4030V	TK4030F	TK4030	TK4040	TK4040M	TK4050	TK4050M	TK4060	
Engine name / Capacity / number of cylinders	(- / cm ³ / -)	F5C / 3200 / 4						NEF / 4500 / 4				
Emissions level		Tier III										
Rated power	[kW/hp(CV)]	48/65	48/65	57/78	57/78	57/78	65/88	65/88	70/95	70/95	74/101	
Maximum torque	(Nm)	290	290	330	330	330	352	352	380	380	410	
Diesel tank capacity	(litres)	83	83	83	83	83	111	111	111	111	111	
Transmission type (1)		8 x 8 Steering-O-Matic™ Plus handle with overcentre engagement										
Max. Speed	(kph)	11	11	11	11	12	12	12	12	12	12	
Transmission type (2)		16 x 8 Steering-O-Matic™ Plus handle with overcentre engagement with creeper										
Max. Speed	(kph)	11	11	11	11	12	12	12	12	12	12	
Maximum number of hydraulic remotes		4					5					
Maximum hydraulic flow	(lpm)	35.5					41.2		45			
Maximum rear lift capacity	(kg)	3535					3720					
PTO Speeds		540 or 540E					540 or 540E, 540 or 1000					
Shoes standard	(mm)	250	300	270	310	350	310	400	310	450	450	
Shoes optional	(mm)	-	270, 310	250	-	-	350	350	350	400	-	
Optional R-Track version (Rubber tracks)	(mm)	-	300	-	300	-	-	-	-	-	-	
Weight in running order ROPS / Cab	(kg)	3270 / -	3340 / -	3280 / -	3360 / -	3580 / -	3990 / 4190	4120 / 4320	4170 / 4370	4300 / 4500	4900 / 5100	
Overall length including front support and rear linkage	(mm)	3173					3252		3339			
Width with standard shoes	(mm)	1150	1300	1170	1310	1450		1700	1410	1750		
Overall height Roll-bar / cab	(mm)	2079 / -			2096 / -	2116 / -	2350 / 1943				2353 / 1943	
Wheelbase with standard shoes	(mm)	1350			1370	1380	1586			1656		