

DAILY MINIBUS

	DAILY CITYS	DAILY CITYS - CNG	DAILY LINE	DAILY LINE	DAILY LINE	DAILY TOURYS	DAILY TOURYS
Engine name / size / number of cylinders	FIC Diesel - 4 cylinders	FIC CNG - 4 cylinders	FIC Diesel - 4 cylinders	FIC Diesel - 4 cylinders	FIC Diesel - 4 cylinders	FIC Diesel - 4 cylinders	FIC Diesel - 4 cylinders
Max. torque	400 Nm at 1350 - 3000 rpm	350 Nm at 1500 - 2730 rpm	400 Nm at 1350 - 3000 rpm	400 Nm at 1350 - 3000 rpm	400 Nm at 1350 - 3000 rpm	400 Nm at 1350 - 3000 rpm	400 Nm at 1350 - 3000 rpm
Displacement	3,0 litres	3,0 litres	3,0 litres	3,0 litres	3,0 litres	3,0 litres	3,0 litres
Power	125 kW (170 hp) at 3500 rpm	100 kW (136 hp) at 3500 rpm	125 kW (170 hp) at 3500 rpm	125 kW (170 hp) at 3500 rpm	125 kW (170 hp) at 3500 rpm	125 kW (170 hp) at 3500 rpm	125 kW (170 hp) at 3500 rpm
Length	7120 mm	7120 mm	5950 mm	7120 mm	7515 mm	7120 mm	7515 mm
Width	2052 mm	2052 mm	2052 mm	2052 mm	2174 mm	2052 mm	2174 mm
Height (with A/C)	2972 mm	2972 mm	2784 mm	2784 mm	2905 mm	2972 mm	3090 mm
Wheelbase	4100 mm	4100 mm	3520 mm (L)	4100 mm	4100 mm (L)	4100 mm	4100 mm (L)
Front / Rear overhang	1008 mm / 2012 mm	1008 mm / 2012 mm	1008 mm / 1422 mm	1008 mm / 2012 mm	1008 mm / 2407 mm	1008 mm / 2012 mm	1008 mm / 2407 mm
Front / Rear track	1724 mm / 1540 mm	1724 mm / 1540 mm	1724 mm / 1540 mm	1724 mm / 1540 mm	1724 mm / 1661 mm	1724 mm / 1540 mm	1724 mm / 1661 mm
Internal height	2080 mm	2080 mm	1820 mm	1820 mm	1820 mm	2010 mm	2010 mm
Front / Middle / Rear door access height	NA/250mm/NA	NA/250mm/NA	260 mm/NA/NA	260 mm/NA/NA	310 mm/NA/NA	260 mm/NA/NA	310 mm/NA/NA
Front / Middle / Rear door width	NA/2086mm/NA	NA/2086mm/NA	647 mm/NA/NA	647 mm/NA/NA	647 mm/NA/NA	647 mm/NA/NA	647 mm/NA/NA
Wall-to-wall turning radius	15190 mm	15190 mm	12744 mm	15190 mm	14758 mm	15190 mm	14758 mm
Kerb-to-kerb turning radius	14564 mm	14564 mm	12084 mm	14564 mm	14108 mm	14564 mm	14108 mm
Approach / departure angles	19.17/22.52	19.17/22.52	19.05°/22.61°	19.17°/22.52°	19.61°/21.62°	19.17°/22.52°	19.61°/21.62°
GVW (max legal permissible weight depending on registration country)	5600 kg	5600 kg	4500 kg	5600 kg	6100 kg	5600 kg	6500 kg
Max. permissible front axle load	2100 kg	2100 kg	2100 kg	2100 kg	2200 kg	2100 kg	2300 kg
Max. permissible middle axle load	-	-	-	-	-	-	-
Max. permissible rear axle load	3700 kg	3700 kg	3100 kg	3700 kg	4200 kg	3700 kg	5000 kg
Emissions level and homologation	EURO VI - EURO III (146 hp)	EURO VI	EURO VI - EURO III (146 hp)	EURO VI - EURO III (146 hp)	EURO VI - EURO III (146 hp)	EURO VI - EURO III (146 hp)	EURO VI - EURO III (146 hp)