

**Kompakt**

MODEL	TRANSMISSION			ENGINE							PTO					
	Synchromesh transmission with 4 ratios in each of 3 groups 12 forward and 12 reverse gear ratios 40 km/h transmission version	2-stage powershift transmission with 4 ratios in each of 3 groups 24 forward and 24 reverse gear ratios 40 km/h transmission version	Synchromesh transmission with mechan. splitter group with 4 ratios in each of 3 groups 24 forward and 24 reverse gear ratios 40 km/h transmission version	Nominal rating ECE R120 <sup>1)</sup> (kW/hp)	Common Rail Turbodiesel with intercooler / level IIIB					PTO shaft speed at engine speed of rpm			Half PTO shaft	Front-mounted PTO shaft (rpm)		
Crawler gear with 20 forwards and 20 reverse gear ratios	Crawler gear with 40 forwards and 40 reverse gear ratios		Nominal speed (rpm)		Maximum torque ECE R120 <sup>1)</sup> (Nm at rpm/min)	Torque increase acc. to OECD (%)	Number of cylinders / cubic cc (cm3)	Fuel tank capacity (litres)	540/540E	540/1,000	540E/1,000					
	with shuttle shift	with Powershuttle	with electrohydraulic Powershuttle	with shuttle shift	with Powershuttle											
4055 KOMPAKT S	■ ○	○ ○	- -	-	-	43 / 58	2,300	244 at 1,500	37	4 / 3,400	90	1,958/1,592	-	-	○	-
4065 KOMPAKT S	■ ○	○ ○	- -	-	-	48 / 65	2,300	275 at 1,500	38	4 / 3,400	90	1,958/1,592	-	-	○	-
4075 KOMPAKT	■ ○	○ ○	○ ○	○	○	55 / 75	2,300	309 at 1,500	36	4 / 3,400	115	1,876/1,535	1,876/2,125	1,535/2,125	○	○
4085 KOMPAKT	■ ○	○ ○	○ ○	○	○	63 / 86	2,300	351 at 1,500	34	4 / 3,400	115	1,876/1,535	1,876/2,125	1,535/2,125	○	○
4095 KOMPAKT	■ ○	○ ○	○ ○	○	○	73 / 99	2,300	407 at 1,500	34	4 / 3,400	115	1,876/1,535	1,876/2,125	1,535/2,125	○	○
4105 KOMPAKT	■ ○	○ ○	○ ○	○	○	79 / 107	2,300	444 at 1,500	35	4 / 3,400	115	1,876/1,535	1,876/2,125	1,535/2,125	○	○
4115 KOMPAKT	■	○	○	○	○	84 / 114	2,300	457 at 1,500	32	4 / 3,400	115	1,876/1,535	1,876/2,125	1,535/2,125	○	○

MODEL	HYDRAULICS						ALL-WHEEL DRIVE / STEERING		TYRES <sup>2)</sup>	WEIGHT* WITH CAB AND 4WD		CAB
	MHR (mechanical hitch regulation)	EHR (electronic hitch regulation)	Max. displacement of tandem pump Hydraulics / steering unit (l/min)	Max. lifting force / continuous lifting force acc. to OECD at 610 mm (kg)	Rear-mounted control units / intermediate axle control units	Front-mounted hydraulics maximum lifting force (kg)	Electro-hydraulic all-wheel drive engagement	Steering lock (°)		Standard tyres*	Unladen weight (kg)	
								Min. turning radius (m)	front rear			
4055 KOMPAKT S	■	-	48 / 36	2,500 / 2,100	3 / 2	-	■	55° 3.82	14.9R20 16.9R30	2,280 4,500		
4065 KOMPAKT S	■	-	48 / 36	2,500 / 2,100	3 / 2	-	■	55° 3.82	14.9R20 16.9R30	2,280 4,500		
4075 KOMPAKT	o	■	64 / 36	3,700 / 3,350	3 / 2	1,670	■	55° 4.33	14.9R20 16.9R30	3,600 6,000		
4085 KOMPAKT	o	■	64 / 36	3,700 / 3,350	3 / 2	1,670	■	55° 4.33	14.9R20 16.9R30	3,600 6,000		
4095 KOMPAKT	o	■	64 / 36	3,700 / 3,350	3 / 2	1,670	■	55° 4.33	14.9R20 16.9R30	3,600 6,000		
4105 KOMPAKT	o	■	64 / 36	3,700 / 3,350	3 / 2	1,670	■	55° 4.33	14.9R20 16.9R30	3,600 6,000		
4115 KOMPAKT	o	■	64 / 36	3,700 / 3,350	3 / 2	1,670	■	55° 4.33	14.9R20 16.9R30	3,600 6,000		

Spacious cab with individually adjustable driver's seat with lumbar support, minimum vibration, max. noise level 75 dB(A), effective heating and air-conditioning systems, wide windscreen and good all-round visibility exhaust pipe up beside the A-pillar, tapered bonnet, roof viewing window, powerful headlight package, ergonomically configured controls, tractor monitor.

■ Standard      o Optional      - Not available

\* Depending on country-specific legislative requirements and specifications

<sup>1)</sup> ECE R120 corresponds to ISO 14396 and 97/68/EG, <sup>2)</sup> other wheel options - refer to price list

---