

Multi

| MODEL | TRANSMISSION | ENGINE | | | | | | POWER TAKE-OFF | | | |
|----------------------------|---|--|-------------------|--|---------------------------------------|---|---------------------------|----------------------------------|-----------------------------|---|-----------------------------|
| | | Rated power ECE (R120 ¹) [kW/hp(CV)] | Rated speed (rpm) | Maximum torque (ECE R120 ¹) (Nm @ rpm) | Torque increase according to OECD (%) | Number of cylinders/displacement (cm ³) | Fuel capacity (litres) | Electro-hydraulically switchable | | | |
| Power take-off speed (rpm) | bei Motordrehzahl (U/min) | | | | | | | Ground-speed power take-off | Front power take-off (rpm) | | |
| | Four-speed Powershift gearbox with Powershuttle, 40 km/h at 1,750 rpm | | | | | | 540/540E/ 1,000/1,000E | | 1,805/1,542/ 1,880/1,606 | | 1,000 at 1,920 engine speed |
| 4095 MULTI | 32 forward and 32 reverse gears | 73 / 99 | 2,200 | 407 bei 1,500 | 34 | 4 / 3,400 | 150 | ■ | ■ | ■ | o |
| 4105 MULTI | 32 forward and 32 reverse gears | 79 / 107 | 2,200 | 444 bei 1,500 | 35 | 4 / 3,400 | 150 | ■ | ■ | ■ | o |
| 4115 MULTI | 32 forward and 32 reverse gears | 84 / 114 | 2,200 | 457 bei 1,500 | 32 | 4 / 3,400 | 150 | ■ | ■ | ■ | o |

| MODELL | HYDRAULICS | | | | | ALL-WHEEL DRIVE / STEERING | | TYRES ²⁾ | WEIGHT* | CAB |
|------------|---------------------------------|---|---|--|--|--|--------------------|---------------------------------|---------------------|--|
| | EHR electronic hitch regulation | Max. hydraulic pump output with OCLS as standard/with CCLS as an option (l/min) | Lift capacity according to OECD at 610 mm with OCLS as standard/with CCLS as an option (kg) | Max number of additional control units mounted at rear/in centre | Built-in front hydraulics – maximum lift capacity (kg) | Electro-hydraulic all-wheel and differential locks – shift | Steering angle (°) | Tyres* fitted as standard front | Unladen weight (kg) | |
| 4095 MULTI | ■ | 60 / 100 | 4,100 / 4,700 | 4 / 2 | 2,250 | ■ | 60° | 480/65 R24 | 4,500 | <p>Access steps on both sides, spacious, unrestricted access, interior noise: 72 dB(A), seat with air suspension, air-conditioning system*, interior lighting, windscreen that opens to 90°, roof window, tinted windows, opening rear window, windscreen wiper/washer system, front and rear work lights on cab roof, central control panel for work lights, intuitive control panel, power monitor</p> <p>Optional: cab suspension, power mirror and heated telescopic rearview mirror, eight LED work lights, rear windscreen wiper/washer system</p> |
| | | | | | | | 4.05 | 540/65 R38 | 7,500 / 7,800 | |
| 4105 MULTI | ■ | 60 / 100 | 4,100 / 4,700 | 4 / 2 | 2,250 | ■ | 60° | 480/65 R24 | 4,500 | |
| | | | | | | | 4.05 | 540/65 R38 | 7,500 / 7,800 | |
| 4115 MULTI | ■ | 60 / 100 | 4,100 / 4,700 | 4 / 2 | 2,250 | ■ | 60° | 480/65 R24 | 4,500 | |
| | | | | | | | 4.05 | 540/65 R38 | 7,500 / 7,800 | |

■ Standard

○ Optional

¹⁾ ECE R120 corresponds to ISO 14396 and 97/68/EG

²⁾ See price list for further wheel options

³⁾ With standard tyres

* According to country-specific regulations and specifications