

T6

		T6.125	T6.145	T6.155	T6.165	T6.175	T6.180
Engine name / Capacity / number of cylinders	(- / cm ³ / -)	Nef / 4485/ 4	Nef / 4485/ 4	Nef / 4486/ 4	Nef / 4487/ 4	Nef / 4488/ 4	Nef/6728 /6
Emissions level		Tier 4B / Stage 4					
Maximum power	[kW/hp(CV)]		107/145	114/155	124/168	129/175	129/175
Rated power	[kW/hp(CV)]	85/115	85/115	92/125	99/135	107/145	107/145
Max. torque - ISO TR14396	(Nm@rpm)	528@1500	528@1500	560@1500	605@1500	650@1500	650@1500
Diesel tank capacity	(litres)	230					
Transmission type (1)		Electro Command™ Transmission					
Max. speed	(kph)	40 / 50					
Transmission type (2)		Auto Command™ Continuously Variable Transmission					
Max. speed	(kph)	40 / 50					
Maximum number of hydraulic remotes		5 electronic and 3 electronic mid-mounts					
Standard Main Pump flow / Pump pressure	(lpm / Bar)	113/210					
Max. lift capacity at ball ends	(kg)	7864					
Maximum front linkage capacity	(kg)	3200					
PTO Speeds		540 / 540E / 1000 / 1000E					
Front PTO Speeds		1000 / 1000E					
Terraglide™ front axle suspension		Standard					
Max. permissible weight	(kg)	10500					
Maximum overall length inc. front and rear linkage	(mm)	5189					
Minimum width	(mm)	2380					3114
Overall height of Comfort Ride™ suspension cab	(mm)	2965	2990	2990	2990	2990	3040

Wheelbase Standard 4WD axle	(mm)	2642
-----------------------------	------	------