

Farmall C

		Farmall 55 C	Farmall 65 C	Farmall 75 C	Farmall 85 C	Farmall 95 C	Farmall 105 C	Farmall 115 C
Engine name / size / number of cylinders	(- / cm ³ / -)	F5C /3,400 / 4						
Emissions level		Tier 4A / Stage IIIB						
Rated power	(hp[CV])	58	65	75	86	99	107	114
Maximum torque	(Nm)	244	275	309	351	407	444	457
Diesel tank capacity	(litres)	90			150L			
Transmission type (1)		12 x 12 Synchroshift with mechanical shuttle (not allowed for 105-115hp)						
Max. Speed	(kph)	40						
Transmission type (2)		12 x 12 Synchroshuttle with Creeper (not allowed for 105-115hp)						
Max. Speed	(kph)	40						
Transmission type (3)		12x12 Power Shuttle						
Max. Speed	(kph)	40						
Transmission type (4)		20 x 20 Synchroshift with power shuttle and creeper						
Max. speed	(kph)	40						
Transmission type (6)		-			24x24 Powershuttle and Splitter			
Max. Speed	(kph)	-			40			
					24 x 24 two speed powershift with PowerShuttle HILO with ECO SPEED			
					40			
Transmission type (7)		-			40x 40 two speed powershift with power shuttle with creeper with ECO SPEED			
Max. Speed	(kph)	-			40			
Maximum number of hydraulic remotes		3 mechanical and two mechanical mid-mounts						
Maximum hydraulic flow	(Litres/minute)	84			Mega pump 37L Service – 64L HPL Remotes l/min			

Maximum rear lift capacity	(kg)	2,500			4270			
PTO Speeds		540, 540E (ground speed optional)			540, 540/1000, 540/540E/1000(less ground speed) 540/540E/1000/ (with ground speed)			
Maximum permissible weight	(kg)	4,500			6200			
		Farmall 55 C	Farmall 65 C	Farmall 75 C	Farmall 85 C	Farmall 95 C	Farmall 105 C	Farmall 115 C
Overall length including weight pack and rear linkage	(mm)	4,001			4147			
Minimum width	(mm)	1,922			1,923			
Overall height with 420/70R30/18,4R34	(mm)	2,378	2,423		2,494		2,594	
Wheelbase	(mm)	2,102			2285			