

T6 Series Tractors

| T6 Series Tractors | | T6.145 | T6.155 | T6.165 | T6.175 | T6.185 |
|--|-----------------------------|---|--------|--------|--------|---------------------|
| Engine name / size / number of cylinders | (- / cm ³ / -) | Turbo Diesel with High Pressure Common Rail with Electronic Fuel Delivery Control | | | | |
| Displacement cu. in. (L) | | 274 cu. in. (4.5L) | | | | 411 cu. in. (6.7 L) |
| Maximum Boosted Engine HP | (hp[CV]) | 145 | 155 | 169 | 175 | 175 |
| Rated Engine HP | (hp[CV]) | 116 | 125 | 135 | 145 | 145 |
| PTO HP | | 95 | 105 | 110 | 120 | 125 |
| Transmission Type (Standard) | | 16 x 16 Electro Command™ semi-power shift | | | | |
| Transmission Type (Option 1) | | 32 x 32 Electro Command™ w/ Creeper | | | | |
| Transmission Type (Option 2) | | 16 x 16 Electro Command™ w/ AutoShift™ | | | | |
| Transmission Type (Option 3) | | 17 x 16 Electro Command™ w/ Autoshift | | | | |
| Maximum number of hydraulic remotes | | 2, 3, or 4 | | | | |
| Maximum hydraulic flow - Standard | (Litres/minute) | 21.1 gpm (80L/min) | | | | |
| Maximum hydraulic flow - Optional | (Litres/minute) | 29.9 gpm (80L/min) | | | | |
| PTO Speeds | | 540/1000 RPM | | | | |
| Lift Capacity - Standard | | 8,338 lbs (3,782 kg) | | | | |
| Lift Capacity - Max Optional | | 11,649 lbs (5,284 kg) | | | | |