

### TS6 Series Tractors

TS6 Series Tractors		TS6.110	TS6.120	TS6.130	TS6.140	TS6.120 High-Clearance
Engine name / size / number of cylinders	(- / cm <sup>3</sup> / -)	4 cylinder, 16 valve, High Pressure Common Rail, Air-to-Air Intercooled Turbo Diesel				4 cylinder, 16 valve, High Pressure Common Rail, Air-to-Air Intercooled Turbo Diesel
Displacement cu. in. (L)		274 (4.5)				
Rated power	(hp[CV])	110 hp	119 hp	130 hp	139 hp	119 hp
PTO HP		90	96	105	115	96
Transmission Type (Standard)		8 x 8 Mechanical Shuttle				
Transmission Type (Option 1)		8 x 8 Hydraulic Shuttle				
Maximum number of hydraulic remotes		2, 3, or 4				
Maximum hydraulic flow - Standard	(Litres/minute)	13 GPM (49L/min)				
Maximum hydraulic flow - Optional	(Litres/minute)	22 GPM (83L/min)				
PTO Speeds		540/1000 RPM				
Lift Capacity - Standard		3,735 lbs (1,694 kg)				
Lift Capacity - Max Optional		7,326 lbs (3,323 kg)				
Ground Clearance (lowest part of front axle w/ 13.6-38 R2 front and rear tires)	in (mm)					25.25 in (616)