

## T4 Series Tractors

T4 Series Tractors		T4.90	T4.100	T4.110	T4.120
Engine name / size / number of cylinders	( - / cm <sup>3</sup> / -)	FPT F5G/4 cylinder diesel			
Displacement	cu. in. (L)	207 (3.4)			
Gross Engine HP	HP	86	99	107	117
PTO HP		73	85	93	99
Transmission Type (Standard)		12 x 12 Mechanical Shuttle			
Transmission type (Option 1)		12 x 12 Power Shuttle			
Transmission type (Option 2)		20 x 20 Power Shuttle w/ Creeper			
Transmission type (Option 3)		24 x 24 Dual Command™			
Transmission type (Option 4)		40 x 40 Dual Command™ w/ Creeper			
Maximum number of hydraulic remotes		2 or 3			
Maximum hydraulic flow - Implement	gpm (litres/min)	21.1 gpm (80L/min)			
Maximum hydraulic flow - Implement	gpm (litres/min)	11.4 gpm (43L/min)			
Base PTO RPM - 12 x 12		540			
Optional PTO RPM - 12 x 12		540/540E or 540/100			540/1000
Base PTO RPM - 24 x 24 DualCommand™		540/540E			
Optional PTO RPM - 24 x 24 DualCommand™		540/1000			
Lift Capacity	lbs(kg)	5,620 (2,549)			