

MODEL	Farmall 30C	Farmall 35C	Farmall 40C	Farmall 45C CVT	Farmall 50C	Farmall 55C CVT	Farmall 65C	Farmall 75C	Farmall 90C	Farmall 100C	Farmall 110C	Farmall 120C
Displacement, cu in (L) / No. of Cylinders	91.3 (1.496) / 3	91.3 (1.496) / 3	135 (2.216) / 4	136 (2.23) / 3	135 (2.216) / 4	136 (2.23) / 3	207 (3.4) / 4	207 (3.4) / 4	207 (3.4) / 4	207 (3.4) / 4	207 (3.4) / 4	207 (3.4) / 4
Rated power (hp)	32hp @ 2600rpm	36hp @ 2600rpm	40hp @ 2600rpm	45hp @ 2600rpm	46hp @ 2600rpm	53hp @ 2600rpm	64hp @ 2300rpm	74hp @ 2300rpm	86hp @ 2300rpm	99hp @ 2300rpm	107hp @ 2300rpm	117hp @ 2300rpm
Maximum Engine Power (hp)	32	36	40	45	46	53	64	74	86	99	107	117
PTO Horsepower with standard options hp	26	29.6	32.4	34	37.3	41	50	65	73	85	93	99
PTO Speeds, rpm	540	540	540	540	540	540	540 std; 540 / 540E opt.	540 std; 540 / 540E opt.	540 std; 540E or 1000 opt.	540 std; 540E or 1000 opt.	540 std; 540E or 1000 opt.	540/540E std; 540/1000 opt.
Aspiration, Turbocharged or Naturally Aspirated	Turbocharged	Turbocharged	Natural	Wastegate Turbocharger, aftercooled	Natural	Wastegate Turbocharger, aftercooled	Wastegate turbocharged	Wastegate turbocharged	Wastegate turbocharged and aftercooled	Wastegate turbocharged and aftercooled	Wastegate turbocharged and aftercooled	Wastegate turbocharged and aftercooled
Standard transmission configuration	12x12 Synchro-shuttle	12x12 Synchro-shuttle	16x16 Synchro-shuttle	Continuously Variable Transmission	16x16 Synchro-shuttle	Continuously Variable Transmission	12x12 Power Shuttle	8x8 Mechanical Shuttle	12x12 Power Shuttle	12x12 Power Shuttle	12x12 Power Shuttle	12x12 Power Shuttle
Maximum Speed Forward, mph (kph)	14.2 (22.9)	14.2 (22.9)	17 (27.3)	18.6 (29.9)	17 (27.3)	18.6 (29.9)	19 (30.6)	20.1 (32.4)	18.6 or 25 (30 or 40)	18.6 or 25 (30 or 40)	18.6 or 25 (30 or 40)	18.6 or 25 (30 or 40)
Creeper Range Available	No	No	No	Yes, with CVT	No	Yes, with CVT	No	Yes	Optional 20x20	Optional 20x20	Optional 20x20	Optional 20x20
Transmission option 1	3-Range Hydrostatic	3-Range Hydrostatic	3-Range Hydrostatic	No option	3-Range Hydrostatic	No option	No option	8x8 Power Shuttle	24x24 Power Shuttle & Hi-Lo	24x24 Power Shuttle & Hi-Lo	24x24 Power Shuttle & Hi-Lo	24x24 Power Shuttle & Hi-Lo
Transmission option 2	No option	No option	No option	No option	No option	No option	No option	12x12 Hydraulic Shuttle	12x12 Synchro Shuttle	12x12 Synchro Shuttle	12x12 Synchro Shuttle	12x12 Synchro Shuttle
Hydraulic System Type	Open center	Open center	Open center	Open Center	Open center	Open Center	Open Center	Open Center	Open center	Open center	Open center	Open center
Standard flow, gpm (Lpm)	7.3 (27.5)	7.3 (27.5)	8.2 (31)	9.7 (36.9)	8.2 (31)	9.7 (36.9)	12.5 (47.5)	12.5 (47.5)	16..9 (64)	16..9 (64)	16..9 (64)	16..9 (64)
Number of Standard Remote Valves	1 or 2 optional	1 or 2 optional	1 or 2 optional	1 or 2 optional	1 or 2 optional	1 or 2 optional	2 std; 3rd dealer install	1 std; 2 opt	2 std; 3rd dealer install	2 std; 3rd dealer install	2 std; 3rd dealer install	2 std; 3rd dealer install
Maximum Lift Capacity 24 Inches behind pin, lb (kg)	1,433 (650)	1,433 (650)	2,469 (1120)	2,800 (1270)	2,469 (1120)	2,800 (1270)	3,664 (1662)	3,664 (1662)	7,351 (3334)	7,351 (3334)	7,351 (3334)	7,351 (3334)
Wheelbase in (mm)	66 (1676)	66 (1676)	73.2 (1860)	73.5 (1867)	73.2 (1860)	73.5 (1867)	83.9 (2132)	83.9 (2132)	90 (2286)	90 (2286)	90 (2286)	90 (2286)
Overall length , in (mm)	119 (3024)	119 (3024)	128.1 (3254)	122 (3098)	128.1 (3254)	122 (3098)	151 (3836)	149 (3785)	160 (4064)	160 (4064)	160 (4064)	160 (4064)



MODEL	Farmall 30C	Farmall 35C	Farmall 40C	Farmall 45C CVT	Farmall 50C	Farmall 55C CVT	Farmall 65C	Farmall 75C	Farmall 90C	Farmall 100C	Farmall 110C	Farmall 120C
Height to Top of Cab/ROPS for non cabbed versions, in (mm)	93.6 (2379)	88.5 (2249)	93.3 (2369)	92.7 (2355)	93.3 (2369)	92.7 (2355)	97.8 (2484)	98 (2489)	102 (2591)	102 (2591)	102 (2591)	102 (2591)
Overall Width, with standard wheels or tracks, in (mm)	66.4 (1687)	66.4 (1687)	69.1 (1755)	68.3 (1735)	69.1 (1755)	68.3 (1735)	75.7 (1922)	83 (2108) across fenders	83 (2108) across fenders	83 (2108) across fenders	83 (2108) across fenders	83 (2108) across fenders
Overall Weight without ballast, lb (kg)	3,218 (1460)	3,589 (1628)	4,380 (1987)	4,940 (2240)	4,380 (1987)	4,940 (2240)	6,239 (2830)	6,239 (2830)	8,157 (3700)	8,157 (3700)	8,157 (3700)	8,157 (3700)