

MODEL	DH253	DH303	DH363	DH403
Cutting width, ft in (m)	25' (7.62)	30' (9.14)	36' (11.0)	40' (12.19)
Center delivery or Double-swath	Center or double	Center or double	Center or double	Center only
Upper Cross Auger	No	Optional	Optional	Optional
Maximum angle, below horizontal, degrees	2 to 8	2 to 8	2 to 8	2 to 8
Weight w/ Reel, lbs (kg)	4,135 (1876)	5,021 (2277)	5,434 (2465)	6,040 (2740)
Single or double knife	Single or dual knife	Single or dual knife	Dual knife only	Dual knife only
Cutting system	Case IH Std or Stub; or Schumacher Easy Cut	Case IH Std or Stub; or Schumacher Easy Cut	Case IH Std or Stub; or Schumacher Easy Cut	Case IH Std or Stub; or Schumacher Easy Cut
Knife speed, strokes per minute	1400	1400	1400	1400
Sickle stroke, in (mm)	3.35 (85)	3.35 (85)	3.35 (85)	3.35 (85)
Reel description	UII 6-bat w/SF or PF; or HCC 6-bat flipover PF	UII 6-bat w/SF or PF; or HCC 6-bat flipover PF	UII 6-bat single or split, or HCC 6-bat flipover	UII 6-bat, split, w/plastic fingers
Reel fore / aft position control	Standard	Standard	Hydraulic, from cab	Standard
Reel speed range, rpm	10 to 75	10 to 75	10 to 75	10 to 75
Belt width, in (mm)	42 (1067)	42 (1067)	42 (1067)	42 (1067)
Belt speed, maximum, ft/min (m/min)	760 (232)	760 (232)	760 (232)	760 (232)
Windrow center delivery width, in (mm)	56 to 72, or 80 (1422 to 1829, or 2032)	56 to 72, or 80 (1422 to 1829, or 2032)	56 to 72, or 80 (1422 to 1829, or 2032)	56 to 72, or 80 (1422 to 1829, or 2032)
Double swath side delivery width, in (mm)	54 to 65 (1372 to 1651)	54 to 65 (1372 to 1651)	54 to 65 (1372 to 1651)	No side delivery