

MODEL	WD1203	WD1903	WD2303
Engine power, hp	126	190	226
Sicklebar (Auger) Headers	Yes	Yes, 16' and 18'	Yes, 16' and 18'
Draper Headers	Yes, 36' max.	Yes	Yes
Rotary Disc Headers	No	Yes, 36' max.	Yes, 16' and 19'
Double Windrow Attachment	No	Optional for specific headers	Optional for specific headers
Hydraulic Header Reverser	Standard	Standard	Standard
Engine Displacement / No. of Cylinders	274 (4.5) / 4	409 (6.7) / 6	409 (6.7) / 6
Rated Engine Power, hp (kW)	126 (94)	190 (142)	226 (169)
Maximum Engine Power, hp (kW)	Same as rated	199 (148)	235 (175)
Transmission type	Hydrostatic, 2-speed std; 3-speed opt.	Hydrostatic, 2-speed std; 3-speed opt.	Hydrostatic, 2-speed std; 3-speed opt.
Maximum field speed, mph (kph)	10.3 (16.6)	11 (17.8)	11 (17.8)
Maximum road speed, mph (kph)	18 (29) std; 24 (39) opt.	18 (29) std; 24 (39) opt.	18 (29) std; 24 (39) opt.
Suspended Rear Axle (engine end)	Optional air springs	Optional air springs	Optional air springs
Cab Suspension	Standard	Standard	Standard
Wheelbase, in (mm)	134.6 (3419)	137.2(3485)	137.2(3485)
Crop clearance, in (mm)	42.5 (1080)	42.5 (1080)	42.5 (1080)
Weight, w/o header (kg)	10,950 (4966)	12,300 (5580)	12,300 (5580)