

MODEL	Nutri-Placer 930, 27.5 Ft.	Nutri-Placer 930, 32.5 Ft.	Nutri-Placer 930, 37.5 Ft.	Nutri-Placer 930, 42.5 Ft.	Nutri-Placer 930, 47.5 Ft.
Working Width, ft	28	33	38	43	48
Ground engagement, Strip-Till or other	Shank-based insertion	Shank-based insertion	Shank-based insertion	Shank-based insertion	Shank-based insertion
Fertilizer material: Dry, Liquid, or Anhydrous	Anhydrous	Anhydrous	Anhydrous	Anhydrous	Anhydrous
Working width, ft-in (m)	27' 6" (8.4)	32' 6" (9.9)	37' 6" (11.4)	42' 6" (12.95)	47' 6" (14.5)
Number of rows	21, 17 or 11 shanks	25, 19 or 13 shanks	29, 21, or 15 shanks	33, 25 or 17 shanks	37, 27, or 19 shanks
Row spacings, in (mm)	15, 20 or 30 (381, 508 or 762)	15, 20 or 30 (381, 508 or 762)	15, 20 or 30 (381, 508 or 762)	15, 20 or 30 (381, 508 or 762)	15, 20 or 30 (381, 508 or 762)
Hookup to tractor, Mounted or Pull-type	Pull-type	Pull-type	Pull-type	Pull-type	Pull-type
Coulter diameter, in (mm)	20 or 24 (508 or 610)	20 or 24 (508 or 610)	20 or 24 (508 or 610)	20 or 24 (508 or 610)	20 or 24 (508 or 610)
Shanks/knives	Rigid or trip shank w/ two-bolt side knife	Rigid or trip shank w/ two-bolt side knife	Rigid or trip shank w/ two-bolt side knife	Rigid or trip shank w/ two-bolt side knife	Rigid or trip shank w/ two-bolt side knife
Sealing discs, closing discs, berm builder, in (mm)	14 or 18 (356 or 457) smooth or notched	14 or 18 (356 or 457) smooth or notched	14 or 18 (356 or 457) smooth or notched	14 or 18 (356 or 457) smooth or notched	14 or 18 (356 or 457) smooth or notched
Toolbar rigid or flexible	3 Section flex, +16, -7 degrees	3 Section flex, +16, -7 degrees	3 Section flex, +16, -7 degrees	3 Section flex, +16, -7 degrees	3 Section flex, +16, -7 degrees
Depth adjustment	Single point	Single point	Single point	Single point	Single point
Power needed, hp (kW)	165 to 220 (123 to 164)	195 to 260 (145 to 194)	225 to 300 (168 to 224)	255 to 340 (190 to 254)	285 to 380 (213 to 283)