

MODEL	Nutri-Placer 940, 50 Ft.	Nutri-Placer 940, 60 Ft.	Nutri-Placer 940, 65 Ft.
Working Width, ft	50	60	65
Ground engagement, Strip-Till or other	Shank-based insertion	Shank-based insertion	Shank-based insertion
Fertilizer material: Dry, Liquid, or Anhydrous	Dry or Anhydrous	Dry or Anhydrous	Dry or Anhydrous
Working width, ft-in (m)	50' (15.2)	60' (18.3)	65' (19.8)
Number of rows	40 15" rows or 20 30" rows	48 15" rows or 24 30" rows	52 15" rows or 26 30" rows
Row spacings, in (mm)	15 or 30 (381 or 762)	15 or 30 (381 or 762)	15 or 30 (381 or 762)
Hookup to tractor, Mounted or Pull-type	Pull-type	Pull-type	Pull-type
Coulter diameter, in (mm)	24 (610) optional for 30" rows only	24 (610) optional for 30" rows only	24 (610) optional for 30" rows only
Shanks/knives	Trip shank w/ two-bolt side knife	Trip shank w/ two-bolt side knife	Trip shank w/ two-bolt side knife
Sealing discs, closing discs, berm builder, in (mm)	18 (457) smooth or notched	18 (457) smooth or notched	18 (457) smooth or notched
Toolbar rigid or flexible	5-section flex	5-section flex	5-section flex
Depth adjustment	Single point	Single point	Single point
Power needed, hp (kW)	300 to 460 (224 to 343)	360 to 550 (268 to 410)	390 to 600 (291 to 447)