



MODEL	DC92	DC102	DC133	DC163
Tongue Type	Side Pull	Side Pull	Center Pivot	Center Pivot
Cutting Width, ft in (m)	9' 2" (2.80)	10' 4" (3.16)	13' (3.96)	16' (4.88)
Cutting Height, in (mm)	0.95 - 3.2 (24 - 81)	1.25 - 3.5 (32 - 89)	0.79 to 2.7 (20 to 69) std; up to 7.8 (198) opt.	0.79 to 2.7 (20 to 69) std; up to 7.8 (198) opt.
Number of Discs	7	8	8	10
Number of Knives per Disc	2	2	2	2
Disc Speed, rpm	3000	3000	2250	2250
Disc Cutting Diameter, in (mm)	19.7 (500)	19.7 (500)	24.3 (618)	24.3 (618)
Windrow / Swath Width, in (mm)	36-72 (914-1830)	36-84 (914-2134)	Windrow 3' to 8' (0.9 to 2.4 m); Swath 10' to 13' (3 to 4 m)	Windrow 3' to 8' (0.9 to 2.4 m); Swath 10' to 13' (3 to 4 m)
Conditioner Type	Flail or Rolls	Flail or Rolls	Roll or Flail	Roll or Flail
Conditioner Drive	4 HB V-belt plus gears	4 HB V-belt plus gears	4 HB V-belt & enclosed gears	4 HB V-belt & enclosed gears
Roll Length, in (mm)	90 (2286)	102 (2591)	125 (3175)	125 (3175)
Roll Diameter, in (mm)	10.4 (264)	10.4 (264)	10.38 (264)	10.38 (264)
Roll Speed, rpm	647	635	750 or 640	750 or 640
Roll Surface Pattern, standard	Intermeshing spiral	Intermeshing spiral	Chevron intermeshing	Chevron intermeshing
Rotor Length, in (mm)	90 (2286)	102 (2591)	125 (3175)	125 (3175)
Rotor Diameter, in (mm)	22 (560)	22 (560)	22 (560)	22 (560)
Rotor Speed, rpm	1016 std; 730 opt	1016 std; 730 opt	1042 std; 752 opt.	1042 std; 752 opt.
Number of Flails	90	100	120	120
Flail Shape	Tapered	Tapered	Tapered	Tapered
Tractor PTO Minimum Hp (kW)	65 (48)	80 (60)	90 (67)	100 (75)
PTO Rated Speed, rpm	540 (6 spline)	540 (6 spline) or 1000 (21 spline)	1000	1000

MODEL	DC92	DC102		DC133	DC163
Number of Hydraulic Remotes	2	2		2	2
Hydraulic Relief Pressure, psi (bar)	1500 (103.4)	1500 (103.4)		1500 (103.4)	1500 (103.4)
Ground Clearance, in (mm)	17 (432)	18 (457)		16.2 (411)	16.2 (411)