



MODEL	RB444	RB455A	RB565	RB455	RB465
Bale max. diameter, ft	4	5	6	5	6
Bale diameter, in (mm)	30 - 48 (762 - 1220)	36 - 60 (914 - 1524)	36 to 72 (914 to 1829)	36 to 60 (914 to 1524)	36 to 72 (914 to 1829)
Bale width, in (mm)	46.5 (1182)	46.5 (1182)	61.5 (1562)	46.5 (1181)	46.5 (118)
Bale chamber, Fixed or Variable	Variable chamber	Variable chamber	Variable chamber	Variable chamber	Variable chamber
Forming mechanism, Belts, Rolls, Chain & slats	5 rolls and 6 belts	5 rolls and 5 belts	5 rolls and 8 belts	6 rolls and 6 belts	6 rolls and 6 belts
Belt width, in (mm)	7 (178)	7 (178)	7 (178)	7 (178)	7 (178)
Belt description	3-ply laced, chevron	3-ply laced, chevron	Premium Laced std; Endless opt.	Premium Laced std; Endless opt.	Premium Laced std; Endless opt.
Cutter-chopper available	None	None	Optional	CropCutter, Bale-Slice or Silage Special optional	CropCutter or Silage Special optional
Bale ejector description	None	Bale ramp optional	Bale ramp spring loaded; hydraulic opt.	Spring-action bale ramp	Spring-action bale ramp; hydraulic opt.
Twine ball storage, quantity	4	4	6 or 8 active, plus up to 4 spare	6 active in front; plus 2 each side opt.	6 active in front; plus 2 each side opt.
Netwrap, meshwrap feature	No option	Optional	Netwrap available	Netwrap optional	Netwrap optional
Pickup working width, in (mm)	60 (1524)	61 (1554)	68 (1730) flare-to-flare	79.5 (2020)	79.5 (2020)

MODEL	RB444		RB455A		RB565		RB455	RB465
Pickup lift, manual or hydraulic	Manual		Manual: Hyd. field installed		Manual or hydraulic		Manual: Hyd. field installed	Manual: Hyd. field installed
PTO speed, rpm	540		540		540 or 1000		540 or 1000	540 or 1000
Tractor power, hp (kW)	40 (30) PTO		40 (30) PTO		80 (60)		60 to 100 (45 to 75)	710 to 105 (52 to 78)