

MODEL	LB334 Standard	LB334 Packer Cutter	LB334 Rotor Cutter	LB434 Standard	LB434 Rotor Cutter	LB434XL Standard	LB434XL Rotor Cutter
Bale width, in (mm)	31.5 (800)	31.5 (800)	31.5 (800)	47.2 (1200)	47.2 (1200)	47.2 (1200)	47.2 (1200)
Bale height, in (mm)	35.4 (900)	35.4 (900)	35.4 (900)	35.4 (900)	35.4 (900)	35.4 (900)	35.4 (900)
Bale length, maximum, in (mm)	108 (2743)	108 (2743)	108 (2743)	108 (2743)	108 (2743)	118 (3000)	118 (3000)
Pickup working width, in (mm)	77.5 (1968)	77.5 (1968)	77.5 (1968)	87.9 (2232)	92.6 (2352)	87.9 (2232)	92.6 (2352)
Cutter knives	None	6	9 or 19 knives, 38 rotor teeth	None	15 or 29 knives, 58 rotor teeth	See Rotor Cutter version	15 or 29, hydraulic activation
Feeder Description	2 packer forks, 6 single tines	3 packer forks, 6 double tines	Rotor, 31.5" (800 mm), "W" tine	3 packer forks, 9 single tines	Rotor, 47.2" (1200 mm), "W" tine	3 packer forks; 9 single tines	Rotor width 47.2" (1200); "W" tine
Plunger speed, Strokes/minute	48	48	48	48	48	48	48
Knotter Type	Double knot	Double knot	Double knot	Double knot	Double knot	Double knot	Double knot
Number of knotters	4	4	4	6	6	6	6
Twine ball storage, quantity	32	32	32	32	32	32	32
Density Control	3-way monitor control	3-way monitor control	3-way monitor control	3-way monitor control	3-way monitor control	AFS Pro 300 or AFS Pro 700	AFS Pro 300 or AFS Pro 700
Tractor Power, hp (kW)	105 (78)	110 (82)	130 (97)	125 (93)	150 (112)	130 (97)	160 (119)