

MODEL	Tiger-Mate 200, Single-Fold	Tiger-Mate 200, Double-Fold	Tiger-Mate 255 Single Fold	Tiger-Mate 255 Double Fold
Working width, minimum, ft-in (m)	18' 6" (5.63)	38' 6" (11.73)	22' 2" (6.8)	37' 5" (11.4)
Working width, maximum, ft-in (m)	38' 6" (11.73)	60' 6" (18.44)	35' 2" (7.8)	60' 1" (18.3)
Total weight, minimum, lb (kg)	5,650 (2563)	13,650 (6192)	8,440 (3828)	15,725 (7133)
Total weight, maximum, lb (kg)	11,600 (5262)	19,600 (8890)	10,440 (4736)	21,860 (9916)
Sizes available	12	9	5	6
Frame configuration	3 Section, Single fold	5 Section, Double fold	Single fold	Double fold
Underframe clearance, in (mm)	25 (635)	25 (635)	25 (635)	25 (635)
Number of ranks	5	5	5	5
Depth control	Positive mechanical crank	Positive mechanical crank	Single point crank	Single point crank
Shank spacing, in (mm)	6 (152)	6 (152)	6.5 (165)	6.5 (165)
Number of shanks, minimum	37	77	41	69
Number of shanks, maximum	77	121	65	111
Standard trip load, lb (kg)	150 (68)	150 (68)	180 (82)	180 (82)
Required power, hp/ft (kw/m)	4 to 7 (10 to 17)	4 to 7 (10 to 17)	4 to 10 (10 to 24)	4 to 10 (10 to 24)
OPTIONAL ATTACHMENTS				
Coil tine harrow, number of tine bars	3 or 4	3 or 4	2-bar or 4-bar Tiger-Tine	2-bar or 4-bar Tiger-Tine

Crumbler or basket reel, trailing or mounted	Crumbler, 14" dia., trailing	Crumbler, 14" dia., trailing		Mounted behind spike-tooth or coil-tine	Mounted behind spike-tooth or coil-tine
Spike harrow, mounted, number of tine bars	5	5		3-bar	3-bar