

MODEL	True Tandem 335VT, Single Fold 3-Section	True Tandem 335VT, Double Fold 5-Section	True Tandem 335 Barracuda, Single Fold 3- Section	True Tandem 330 Turbo
Fore-aft configuration	Blade-Blade-Rolling reel	Blade-Blade-Rolling reel	Blade-Blade-Rolling reel	Blade-Blade-Rolling basket
Primary blade type, disk, coulter or turbo	Wave blade	Wave blade	Serrated, mdified wave turbo blade	Turbo Coulter
Working width, minimum,ft-in (m)	22' 2" (6.76)	42' 5" (12.93)	22' 5" (6.83)	22' 2" (6.76)
Working width, maximum, ft-in (m)	34' 8" (10.57)	47' 2" (14.38)	34' 3" (10.44)	47' 2" (14.38)
Sizes available, number of widths	5	2	5	6
Blade diameter, in (mm)	20 (508)	20 (508)	22 (559)	20 (508)
Blade spacing, in (mm)	7.5 (191)	7.5 (191)	7.5 (191)	7.5 (191)
Blade edge profile	Wave pattern, can be sharpened	Wave pattern, can be sharpened	Chisel-tip blade serrations	Turbo pattern
Blade concavity	Slight concavity	Slight concavity	Shallow concavity	Shallow concavity
Blade Mounting, on Gangs or Standards	Gangs	Gangs	Gangs	Gangs
Front angle of gang or blades, degrees	18	18	18	18
Rear angle of gang or blades, degrees	18	18	18	18
Description, basket, reel or chopper	Double Edge Rolling Reel	Rolling Reel	Double Edge Rolling Reel	Basket
Rolling Diameter, in (mm)	np	14 (356)	14 (356)	14 (356)
Bars or blades on circumference	Formed double edge on each bar	Flat or round bars, spiral pattern	Formed double edge on each bar	Flat or round bars, spiral pattern

MODEL	True Tandem 335VT, Single Fold 3-Section	True Tandem 335VT, Double Fold 5-Section	True Tandem 335 Barracuda, Single Fold 3- Section	True Tandem 330 Turbo
Harrow tooth, spike or coil tine	Coil tine optional, for rice areas only	Coil tine optional, for rice areas only	Coil tine optional, for rice areas only	Coil tine optional
Power per width of cut, hp/ft (kW/m)	7 to 11 (17 to 27)	7 to 11 (17 to 27)	10 to 15 (24 to 37)	7 to 11 (17 to 27)