

Make	Case IH Early Riser	Case IH Early Riser	Case IH Early Riser
Model	2150 Front-Fold 16Row 30	2150 Front-Fold 12Row 30	2150 Front-Fold 24Row 30
Number of rows	16	12	24
Row spacings, in (mm)	30 (762)	30 (762)	30 (762)
Bulk-Fill or Individual Row Hoppers	Two Bulk-Fill Hoppers	Two Bulk-Fill Hoppers	Two Bulk-Fill Hoppers
Hookup to tractor	Trailing	Trailing	Trailing
Standard hopper capacity, per hopper, bu (L)	Two @ 50 (1762) each	Two @ 50 (1762) each	Two @ 60 (2114) each
Dry Fertilizer capacity, lb (kg)	No option	No option	No option
Liquid Fertilizer capacity, gal (L)	One 400 (1514) opt. w/Bulk Fill; One 600 (2271) opt. w/RH	One 400 (1514) opt. w/Bulk Fill; One 600 (2271) opt. w/RH	One 400 (1514) opt. w/Bulk Fill; One 600 (2271) opt. w/RH
Granular chemical capacity, lb (kg)	Optional AMVAC SmartBox w/in-furrow delivery	Optional AMVAC SmartBox w/in-furrow delivery	Optional AMVAC SmartBox w/in-furrow delivery
Standard Metering device	Precision Planting vSet 2 vacuum meter	Precision Planting vSet 2 vacuum meter	Precision Planting vSet 2 vacuum meter
Furrow-forming device	15" offset discs	15" offset discs	15" offset discs
Depth gauging system	Adjustable T-handle, 1/4" or 1/8th" increments	Adjustable T-handle, 1/4" or 1/8th" increments	Adjustable T-handle, 1/4" or 1/8th" increments
Closing system	9" (229) Inverted discs and press wheel	9" (229) Inverted discs and press wheel	9" (229) Inverted discs and press wheel
Standard down force method	Adjustable air-down, controlled by AFS Pro 700	Adjustable air-down, controlled by AFS Pro 700	Adjustable air-down, controlled by AFS Pro 700
Optional down force method	Precision Planting DeltaForce, hydraulic, row by row	Precision Planting DeltaForce, hydraulic, row by row	Precision Planting DeltaForce, hydraulic, row by row
Standard seed drive	Precision Planting vDrive electric motor, each row	Precision Planting vDrive electric motor, each row	Precision Planting vDrive electric motor, each row
Liquid fertilizer openers	In-furrow optional, ahead of closing discs	In-furrow optional, ahead of closing discs	In-furrow optional, ahead of closing discs
Monitor Options	AFS Pro 700	AFS Pro 700	AFS Pro 700
Number of frame sections	3	3	3

Model	2150 Front-Fold 16Row 30	2150 Front-Fold 12Row 30	2150 Front-Fold 24Row 30
Frame rigid or flexible	Wing flex, +/- 21 degrees	Wing flex, +/- 21 degrees	Wing flex, +/- 21 degrees
Planting width, ft-in, (m)	40' (12.19)	30' (9.14)	60' (18.29)
Power needed, minimum, hp (kW)	180 to 380 (134 to 283)	155 to 310 (116 to 231)	280 to 500 (209 to 373)
PTO driven pump or Power Beyond	22 gpm PTO pump optional	22 gpm PTO pump optional	22 gpm PTO pump optional
Number of remote hydraulic circuits	3 or 4 remote valves and 1 case drain port	3 remote valves and 1 case drain port	3 or 4 remote valves and 1 case drain port