

MODEL	Steiger 370	Steiger 420	Steiger 470	Steiger 500	Steiger 540	Steiger 580 Wheeled	Steiger 620 Wheeled
Displacement, cu in (L) / No. of Cylinders	531 (8.7) / 6	787 (12.9) / 6	787 (12.9) / 6	787 (12.9) / 6	787 (12.9) / 6	787 (12.9) / 6	787 (12.9) / 6
Rated power (hp)	370hp @ 2000rpm	420hp @ 2100rpm	470hp @ 2100rpm	500hp @ 2100rpm	535hp @ 2100rpm	580hp @ 2100rpm	620hp @ 2100rpm
Maximum Engine Power (hp)	405	462	517	550	605	638	682
Power Boost, hp	35	42	47	50	70	58	62
PTO Horsepower with standard options hp	311	355	405	435	473	473	473
PTO Speeds, rpm	1000	1000	1000	1000	1000	1000	1000
Aspiration, Turbocharged or Naturally Aspirated	VGT Turbocharged, Aftercooled	Wastegate Turbocharged, Aftercooled	Wastegate Turbocharged, Aftercooled	Wastegate Turbocharged, Aftercooled	Two-Stage Turbocharged, Inter- & Aftercooled	Two-Stage Turbocharged, Inter- & Aftercooled	Two-Stage Turbocharged, Inter- & Aftercooled
Standard transmission configuration	16F x 2R Full Powershift	16F x 2R Full Powershift	16F x 2R Full Powershift	16F x 2R Full Powershift	16F x 2R Full Powershift	16F x 2R Full Powershift	16F x 2R Full Powershift
Maximum Speed Forward, mph (kph)	25 (40)	25 (40)	25 (40)	25 (40)	25 (40)	25 (40)	25 (40)
Hydraulic System Type	Pressure Flow Compensated	Pressure Flow Compensated	Pressure Flow Compensated	Pressure Flow Compensated	Pressure Flow Compensated	Pressure Flow Compensated	Pressure Flow Compensated
Standard flow, gpm (Lpm)	40 (151)	42 (159)	42 (159)	42 (159)	42 (159)	42 (159)	42 (159)
Optional Pump Flow, gpm (Lpm)	55 (208); 108 (409)	57 (216); 113 (428)	57 (216); 113 (428)	57 (216); 113 (428)	57 (216); 113 (428)	57 (216); 113 (428)	57 (216); 113 (428)
Number of Standard Remote Valves	4 std; up to 8 total	4 std; up to 8 total	4 std; up to 8 total	4 std; up to 8 total	4 std; up to 8 total	4 std; up to 8 total	4 std; up to 8 total
Maximum Lift Capacity 24 Inches behind pin, lb (kg)	20,000 (9072)	20,000 (9072)	20,000 (9072)	19,621 (8900)	19,621 (8900)	19,621 (8900)	19,621 (8900)

MODEL	Steiger 370	Steiger 420	Steiger 470	Steiger 500	Steiger 540	Steiger 580 Wheeled	Steiger 620 Wheeled
Wheelbase in (mm)	148 (3759)	148 (3759)	148 (3759)	154 (3912)	154 (3912)	154 (3912)	154 (3912)
Overall length , in (mm)	291 (7393)	291 (7393)	291 (7393)	300 (7615)	300 (7615)	300 (7615)	300 (7615)
Height to Top of Cab/ROPS for non cabbed versions, in (mm)	151.3 (3843)	151.3 (3843)	151.3 (3843)	156 (3963)	156 (3963)	156 (3963)	156 (3963)
Overall Width, with standard wheels or tracks, in (mm)	120 (3048) bar axles	120 (3048) bar axles	120 (3048) bar axles	120 (3048) bar axles	120 (3048) bar axles	120 (3048) bar axles	120 (3048) bar axles
Overall Weight without ballast, lb (kg)	38,759 (17581)	40,159 (18216)	40,159 (18216)	43,855 (19892)	43,855 (19892)	48,147 (21839)	48,147 (21839)