

MODEL	Steiger 420 Rowtrac	Steiger 470 Rowtrac	Steiger 500 Rowtrac
Displacement, cu in (L) / No. of Cylinders	787 (12.9) / 6	787 (12.9) / 6	787 (12.9) / 6
Rated power (hp)	420hp @ 2100rpm	470hp @ 2100rpm	500hp @ 2100rpm
Maximum Engine Power (hp)	462	517	550
Power Boost, hp	42	47	50
PTO Horsepower with standard options hp	355	405	435
PTO Speeds, rpm	1000	1000	1000
Aspiration, Turbocharged or Naturally Aspirated	Wastegate Turbocharged, Aftercooled	Wastegate Turbocharged, Aftercooled	Wastegate Turbocharged, Aftercooled
Standard transmission configuration	16F x 2R Full Powershift	16F x 2R Full Powershift	16F x 2R Full Powershift
Maximum Speed Forward, mph (kph)	25 (40)	25 (40)	25 (40)
Hydraulic System Type	Pressure Flow Compensated	Pressure Flow Compensated	Pressure Flow Compensated
Standard flow, gpm (Lpm)	42 (159)	42 (159)	42 (159)
Optional Pump Flow, gpm (Lpm)	57 (216); 113 (428)	57 (216); 113 (428)	57 (216); 113 (428)
Number of Standard Remote Valves	4 std; up to 8 total	4 std; up to 8 total	4 std; up to 8 total
Maximum Lift Capacity 24 Inches behind pin, lb (kg)	20,000 (9072)	20,000 (9072)	20,000 (9072)
Wheelbase in (mm)	160 (4064)	160 (4064)	160 (4064)
Overall length , in (mm)	315 (8001)	315 (8001)	315 (8001)
Height to Top of Cab/ROPS for non cabbed versions, in (mm)	151.3 (3843)	151.3 (3843)	151.3 (3843)
Overall Width, with standard wheels or tracks, in (mm)	96 (2438) min; 144 (3658) max	96 (2438) min; 144 (3658) max	96 (2438) min; 144 (3658) max
Overall Weight without ballast, lb (kg)	43,510 (19736)	43,510 (19736)	43,510 (19736)