

MODEL	Steiger 470 Quadtrac	Steiger 500 Quadtrac	Steiger 540 Quadtrac	Steiger 580 Quadtrac	Steiger 620 Quadtrac
Displacement, cu in (L) / No. of Cylinders	787 (12.9) / 6	787 (12.9) / 6	787 (12.9) / 6	787 (12.9) / 6	787 (12.9) / 6
Rated power (hp)	470hp @ 2100rpm	500hp @ 2100rpm	535hp @ 2100rpm	580hp @ 2100rpm	620hp @ 2100rpm
Maximum Engine Power (hp)	517	550	605	638	682
Power Boost, hp	47	50	70	58	62
PTO Horsepower with standard options hp	405	435	473	473	473
PTO Speeds, rpm	1000	1000	1000	1000	1000
Aspiration, Turbocharged or Naturally Aspirated	Wastegate Turbocharged, Aftercooled	Wastegate Turbocharged, Aftercooled	Two-Stage Turbocharged, Inter- & Aftercooled	Two-Stage Turbocharged, Inter- & Aftercooled	Two-Stage Turbocharged, Inter- & Aftercooled
Standard transmission configuration	16F x 2R Full Powershift	16F x 2R Full Powershift	16F x 2R Full Powershift	16F x 2R Full Powershift	16F x 2R Full Powershift
Maximum Speed Forward, mph (kph)	25 (40)	25 (40)	25 (40)	25 (40)	25 (40)
Hydraulic System Type	Pressure Flow Compensated	Pressure Flow Compensated	Pressure Flow Compensated	Pressure Flow Compensated	Pressure Flow Compensated
Standard flow, gpm (Lpm)	42 (159)	42 (159)	42 (159)	42 (159)	42 (159)
Optional Pump Flow, gpm (Lpm)	57 (216); 113 (428)	57 (216); 113 (428)	57 (216); 113 (428)	57 (216); 113 (428)	57 (216); 113 (428)
Number of Standard Remote Valves	4 std; up to 8 total	4 std; up to 8 total	4 std; up to 8 total	4 std; up to 8 total	4 std; up to 8 total
Maximum Lift Capacity 24 Inches behind pin, lb (kg)	20,000 (9072)	19,728 (8949)	19,728 (8949)	19,728 (8949)	19,728 (8949)
Wheelbase in (mm)	154 (3912)	154 (3912)	154 (3912)	154 (3912)	154 (3912)

Overall Weight without ballast, lb (kg)	46,500 (21092)	46,500 (21092)	47,780 (21673)	48,780 (22126)	48,780 (22126)
---	----------------	----------------	----------------	----------------	----------------