

MODEL	Farmall 30A	Farmall 35A	Farmall 50A	Farmall 60A	Farmall 70A	Farmall 110A	Farmall 120A	Farmall 130A	Farmall 140A
Engine Displacement, cu in (L) / No. of Cylinders	91.3 (1.496) / 3	91.3 (1.496) / 3	135.9 (2.23) / 3	135.9 (2.23) / 3	135.9 (2.23) / 3	274 (4.5) / 4	274 (4.5) / 4	274 (4.5) / 4	274 (4.5) / 4
Rated power (hp)	32hp @ 2600rpm	36hp @ 2600rpm	53hp @ 2700rpm	60hp @ 2700rpm	70hp @ 2700rpm	110hp @ 2200rpm	120hp @ 2200rpm	130hp @ 2200rpm	140hp @ 2200rpm
Maximum Engine Power (hp)	32	36	53	60	70	110	120	130	140
PTO Horsepower with standard options hp	27.4	30.7	45	51	61	90	96	105	115
PTO Speeds, rpm	540	540	540 std; 540/540E opt.	540 std; 540/540E opt.	540 std; 540/540E opt.	540 / 1000	540 / 1000	540 / 1000	540 / 1000
Aspiration, Turbocharged or Naturally Aspirated	Turbocharged	Turbocharged	Wastegate turbocharged	Wastegate turbocharged	Wastegate turbocharged	Turbo-intercooled	Turbo-intercooled	Turbo-intercooled	Turbo-intercooled
Standard transmission configuration	12x12 Gear w/ Synchronized Shuttle	12x12 Gear w/ Synchronized Shuttle	8Fx8R Mechanical Shuttle	8Fx8R Mechanical Shuttle	8Fx8R Mechanical Shuttle	8Fx8R Power Shuttle	8Fx8R Power Shuttle	8Fx8R Power Shuttle	8Fx8R Power Shuttle
Maximum Speed Forward, mph (kph)	14.2 (22.9)	14.2 (22.9)	np	np	np	18.6 or 25 (30 or 40)	18.6 or 25 (30 or 40)	18.6 or 25 (30 or 40)	18.6 or 25 (30 or 40)
Creeper Range Available	No	No	No	No	No	Optional for all transmissions	Optional for all transmissions	Optional for all transmissions	Optional for all transmissions
Transmission option 1	3-Range Hydrostatic	3-Range Hydrostatic	No option	No option	No option	16Fx8R Power Shuttle	16Fx8R Power Shuttle	16Fx8R Power Shuttle	16Fx8R Power Shuttle
Transmission option 2	No option	No option	No option	No option	No option	8Fx8R Mechanical Shuttle	8Fx8R Mechanical Shuttle	8Fx8R Mechanical Shuttle	8Fx8R Mechanical Shuttle
Hydraulic System Type	Open center	Open center	Open Center	Open Center	Open Center	Open center system, CCLS remotes	Open center system, CCLS remotes	Open center system, CCLS remotes	Open center system, CCLS remotes
Standard flow, gpm (Lpm)	8.2 (31)	8.2 (31)	11.9 (45)	11.9 (45)	11.9 (45)	22 (83)	22 (83)	22 (83)	22 (83)
Number of Standard Remote Valves	1 or 2 optional	1 or 2 optional	1 std.; 2nd opt.	1 std.; 2nd opt.	1 std.; 2nd opt.	2 std; 3 or 4 opt	2 std; 3 or 4 opt	2 std; 3 or 4 opt	2 std; 3 or 4 opt
Maximum Lift Capacity 24 Inches behind pin, lb (kg)	1,433 (650)	1,433 (650)	2,701 (1225) OECD	2,701 (1225) OECD	2,701 (1225) OECD	7,200 (3266)	7,200 (3266)	7,200 (3266)	7,200 (3266)
Wheelbase in (mm)	67.5 (1715)	67.5 (1715)	97.6 (2478)	97.6 (2478)	97.6 (2478)	99.2 (2520)	99.2 (2520)	103.9 (2640)	103.9 (2640)
Overall length , in (mm)	121 (3074)	121 (3074)	134 (3404)	134 (3404)	134 (3404)	184.6 (4690)	184.6 (4690)	184.6 (4690)	184.6 (4690)

MODEL	Farmall 30A	Farmall 35A	Farmall 50A	Farmall 60A	Farmall 70A	Farmall 110A	Farmall 120A	Farmall 130A	Farmall 140A
Height to Top of Cab/ROPS for non cabbed versions, in (mm)	87.7 (2227)	87.7 (2227)	92.7 (2365)	97.4 (2473)	97.4 (2473)	110 (2800)	110 (2800)	110 (2800)	110 (2800)
Overall Width, with standard wheels or tracks, in (mm)	66.5 (1689)	66.5 (1689)	67.5 (1714)	67.5 (1714)	67.5 (1714)	74.5 (1893) at fenders; 98 (2490) bar axle ends	74.5 (1893) at fenders; 98 (2490) bar axle ends	74.5 (1893) at fenders; 98 (2490) bar axle ends	74.5 (1893) at fenders; 98 (2490) bar axle ends
Overall Weight without ballast, lb (kg)	3,067 (1391)	3,067 (1391)	4,079 (1850)	4,079 (1850)	4,079 (1850)	10,445 (4738)	10,445 (4738)	10,605 (4810)	10,605 (4810)