

MODEL	Magnum 310 Rowtrac	Magnum 340 Rowtrac	Magnum 380 Rowtrac
Displacement, cu in (L) / No. of Cylinders	531 (8.7) / 6	531 (8.7) / 6	531 (8.7) / 6
Rated power (hp)	310hp @ 2000rpm	340hp @ 200rpm	380hp @ 2000rpm
Maximum Engine Power (hp)	380	410	435
Power Boost, hp	70	70	55
PTO Horsepower with standard options hp	265	290	315
PTO Speeds, rpm	540 / 1000	540 / 1000	540 / 1000
Aspiration, Turbocharged or Naturally Aspirated	eVGT Turbocharged, Aftercooled	eVGT Turbocharged, Aftercooled	eVGT Turbocharged, Aftercooled
Standard transmission configuration	18F/4R Powershift	18F/4R Powershift	CVT
Maximum Speed Forward, mph (kph)	25 (40)	25 (40)	25 (40)
Creeper Range Available	No	No	Standard in CVT
Transmission option 1	No option	CVT	No option
Hydraulic System Type	Pressure-flow compensating (PFC)	Pressure-flow compensating (PFC)	Pressure-flow compensating (PFC)
Standard flow, gpm (Lpm)	44 (166)	44 (166)	44 (166)
Optional Pump Flow, gpm (Lpm)	59 (224) or 75 (282)	59 (224) or 75 (282)	59 (224) or 75 (282)
Number of Standard Remote Valves	4 std; 5 or 6 opt	4 std; 5 or 6 opt	4 std; 5 or 6 opt
Maximum Lift Capacity 24 Inches behind pin, lb (kg)	19,900 (9026), quick coupler	19,900 (9026), quick coupler	19,900 (9026), quick coupler

<b>MODEL</b>	<b>Magnum 310 Rowtrac</b>	<b>Magnum 340 Rowtrac</b>	<b>Magnum 380 Rowtrac</b>
Wheelbase in (mm)	124 (3150)	124 (3150)	124 (3150)
Overall length , in (mm)	249 (6332)	249 (6332)	249 (6332)
Height to Top of Cab/ROPS for non cabbed versions, in (mm)	136 (3450)	136 (3450)	136 (3450)
Overall Width, with standard wheels or tracks, in (mm)	93 (2362) min.; 182 (4623) max.	93 (2362) min.; 182 (4623) max.	93 (2362) min.; 182 (4623) max.
Overall Weight without ballast, lb (kg)	36,006 (16332)	36,006 (16332) PS; 37,728 (17113) CVT	37,728 (17113)