

MODEL (Model Years)	Axial-Flow 7240	Axial-Flow 8240	Axial-Flow 9240
SIZE CLASS	7	8	9
Number of Cylinders	6	6	6
Engine Displacement / No. of Cylinders	678 (11.1) / 6	787 (12.9) / 6	972 (15.9) / 6
Horsepower, Rated - hp	402	480	550
Horsepower, Maximum - hp (kW)	468	555	625
Power Boost - hp (kW)	66	75	75
Feeder Width - in (mm)	54 (1372)	54 (1372)	54 (1372)
Threshing System Type	Single longitudinal rotor	Single longitudinal rotor	Single longitudinal rotor
Rotor in (mm)	30 (762)	30 (762)	30 (762)
Rotor - in (mm)	102.8 (2612)	103.3 (2623)	103.3 (2623)
Rotor or Cylinder Speed Range - rpm	220 - 1180	220 - 1180	220 - 1180
Threshing Area Wrap - degrees	180	180	180
Total Sieve Area - sq in (sq m)	10,075 (6.50)	10,075 (6.50)	10,075 (6.50)
Leveling System Available	Standard	Standard	Standard
Unloading Rate - bu/sec. (L/Sec)	4.0 (141)	4.0 (141)	4.5 (159)
Unloading Auger Length, Standard - ft-in (m)	28' 9" (8.8)	28' 9" (8.8)	28' 9" (8.8)
Optional Auger Length - ft-in (m)	23' 6" to 34' (7.2 to 10.4)	23' 6" to 34' (7.2 to 10.4)	23' 6" to 34' (7.2 to 10.4)
Rubber Tracks Available	30" or 36" Factory Fit	30" or 36" Factory Fit	30" or 36" Factory Fit