

MODEL	Farmall 80V Vineyard	Farmall 110V Vineyard
Displacement, cu in (L)	207 (3.4) / 4	207 (3.4) / 4
Rated power (hp)	74hp @ 2300rpm	106hp @ 2300rpm
Maximum Engine Power (hp)	74	106
PTO Horsepower with standard options hp	65	9
PTO Speeds, rpm	540/540E std.; 540/1000 opt.	540/540E std.; 540/1000 opt.
Aspiration, Turbocharged or Naturally Aspirated	Turbocharged, air-to-air aftercooled	Turbocharged, air-to-air aftercooled
Standard transmission configuration	16x16 Mechanical Synchro Shuttle	16x16 Mechanical Synchro Shuttle
Maximum Speed Forward, mph (kph)	19 or 25 (30 or 40)	19 or 25 (30 or 40)
Creeper Range Available	28x16 option	28x16 option
Transmission option 1	16 x16 Power Shuttle	16 x16 Power Shuttle
Transmission option 2	32 x 16 Dual Command	32 x 16 Dual Command
Hydraulic System Type	Open Center	Open Center
Standard flow, gpm (Lpm)	16.9 (64)	16.9 (64)
Optional Pump Flow, gpm (Lpm)	21.1 (80) cab only	21.1 (80) cab only
Number of Standard Remote Valves	2 or 3 rear; 2 mid	2 or 3 rear; 2 mid
Maximum Lift Capacity 24 Inches behind pin, lb (kg)	3,780 (1715)	3,780 (1715)
Wheelbase in (mm)	96 (2438)	96 (2438)
Overall length , in (mm)	148.8 (3779)	148.8 (3779)
Height to Top of Cab/ROPS for non cabbed versions, in (mm)	91.7 (2329)	91.7 (2329)
Overall Width, with standard wheels or tracks, in (mm)	42.5 to 49 (1079 to 1245)	42.5 to 49 (1079 to 1245)
Overall Weight without ballast, lb (kg)	5,975 (2710)	6,151 (2790)