

MODEL	Nutri-Tiller 955 Strip-Till, 8-Row	Nutri-Tiller 955 Strip-Till, 12-Row	Nutri-Tiller 955 Strip-Till, 16-Row	Nutri-Tiller 955 Strip-Till, 24-Row
Fertilizer material: Dry, Liquid, or Anhydrous	Dry, Liquid or Anhydrous	Dry, Liquid or Anhydrous	Dry, Liquid or Anhydrous	Dry, Liquid or Anhydrous
Working width, ft-in (m)	20' (6.1)	30' (9.1)	40' (12.2)	60' (18.3)
Number of rows	8	12	16	24
Row spacings, in (mm)	30 (762)	30 (762)	30 (762)	30 (762)
Coulter diameter, in (mm)	24 (610) optional	24 (610) optional	24 (610) optional	24 (610) optional
Residue tine wheels, Row cleaners	With adjustable down pressure spring	With adjustable down pressure spring	With adjustable down pressure spring	With adjustable down pressure spring
Shanks/knives	HCS ST, spring reset shank; 2-plate knife adapter	HCS ST, spring reset shank; 2-plate knife adapter	HCS ST, spring reset shank; 2-plate knife adapter	HCS ST, spring reset shank; 2-plate knife adapter
Shank trip force, lb (kg)	850 or 1,250 (386 or 567)	850 or 1,250 (386 or 567)	850 or 1,250 (386 or 567)	850 or 1,250 (386 or 567)
Sealing discs, closing discs, berm builder, in (mm)	18 (457) smooth or notched	18 (457) smooth or notched	18 (457) smooth or notched	18 (457) smooth or notched
Conditioning basket, in (mm)	14 (356) Flat or concave optional	14 (356) Flat or concave optional	14 (356) Flat or concave optional	14 (356) Flat or concave optional
Toolbar rigid or flexible	Rigid	Wing flex, +16, -7 degrees	Wing flex, +16, -7 degrees	Inner +20, -9; outer +7, -7 deg.
Depth adjustment	Single point, crank adjust	Single point, crank adjust	Single point, crank adjust	Single point, crank adjust
Power needed, hp (kW)	150 to 200 (112 to 149)	225 to 300 (168 to 224)	300 to 400 (224 to 298)	450 to 620 (336 to 462)