

| MODEL | Nutri-Tiller 5310, 6-Row, Advanced Row Unit | Nutri-Tiller 5310, 8-Row, Advanced Row Unit | Nutri-Tiller 5310 Strip-Till, 6-Row | Nutri-Tiller 5310 Strip-Till, 8-Row |
|---|--|--|--|--|
| Fertilizer material: Dry, Liquid, or Anhydrous | Dry, Liquid or Anhydrous | Dry, Liquid or Anhydrous | Dry, Liquid or Anhydrous | Dry, Liquid or Anhydrous |
| Working width, ft-in (m) | 15' (4.6) | 20' (6.1) | 15' (4.6) | 20' (6.1) |
| Number of rows | 6 | 8 | 6 | 8 |
| Row spacings, in (mm) | 30 (762) | 30 (762) | 30 (762) | 30 (762) |
| Coulter diameter, in (mm) | 24 (610) | 24 (610) | 24 (610) | 24 (610) |
| Residue tine wheels, Row cleaners | With adjustable down pressure spring | With adjustable down pressure spring | Optional | Optional |
| Shanks/knives | HCS ST, spring reset shank; 2-plate knife adapter | HCS ST, spring reset shank; 2-plate knife adapter | Spring reset or rigid shank | Spring reset or rigid shank |
| Shank trip force, lb (kg) | 850 or 1,250 (386 or 567) | 850 or 1,250 (386 or 567) | 850 or 1,250 (386 or 567) | 850 or 1,250 (386 or 567) |
| Sealing discs, closing discs, berm builder, in (mm) | 18 (457) smooth or notched | 18 (457) smooth or notched | 18 (457) smooth | 18 (457) smooth |
| Conditioning basket, in (mm) | 14 (356) Flat or concave optional | 14 (356) Flat or concave optional | 14 (356) Flat or concave optional | 14 (356) Flat or concave optional |
| Toolbar rigid or flexible | Rigid | Rigid | Rigid | Rigid |
| Depth adjustment | Gauge wheels optional | Gauge wheels optional | Pin adjust wheels | Pin adjust wheels |
| Power needed, hp (kW) | 120 to 150 (90 to 112) | 150 to 200 (112 to 149) | 120 to 150 (90 to 112) | 150 to 200 (112 to 149) |